

TABLE OF CONTENTS

<i>Drawing Number</i>	<i>Sanitary Sewer Drawings</i>
301	Concrete Pipe Allowable Installation Depth
302	Industrial Manhole Frame – 7" Depth
303	Manhole Adapter (Sand Collar)
304	Not used
305	Sanitary and Storm Manhole Cover
306	Sanitary and Storm Manhole Tamperproof Cover
307	Sanitary and Storm Tamperproof Manhole Frame
308	Sanitary and Storm Manhole Waterproof Cover
309	Sanitary and Storm Waterproof Manhole Frame
310	Sanitary Sewer Connection, 3 or 4 Lots w/ Private Easement
311	Sanitary Sewer Connection, 5 or more Lots w/ Public Easement
312	Sanitary Sewer Connection, Two Single Family Lots
313	Sanitary Sewer Connection, Single Family
314	Service Branch
315	Sanitary and Storm Pipe Zone Bedding and Backfill
316	Sewer Pipe Anchor Wall
317	Sewer Pipe Concrete Encasement
318	Shallow Inside Drop Manhole
319	Shallow Manhole For 27" and Lesser Diameter Pipes
320	Siamese Service Branch
321	Standard Cleanout
322	Standard Inside Drop Manhole
323	Standard Manhole for 27" and Lesser Diameter Pipes
324	Standard Manhole for 30" and Larger Diameter Pipes
325	Standard Sampling Manhole
326	Suburban Manhole Frame 3" Depth
327	Tap in Existing Sewer Main For Service Branch
328	Typical Trench Section Backfill and Surfacing
329	Typical Trench Section Backfill and Surfacing
<i>Drawing Number</i>	<i>Water Works Drawings</i>
401	Standard Fire Hydrant Assembly
402	Standard Trench Section
403	Standard 1" Water Service
404A	Standard 2" Service – Irrigation (1 ½" – 2" Meter)
404B	Standard 2" Service – Domestic with or w/o Irrigation (1 ½" – 2" Meter)
404C	Standard 2" Service – Domestic with or w/o Irrigation (1 ½" – 2" Meter)

405	Standard Water Sampling Station
406	Standard Combination Air Valve Unit
407A	Standard 2" Blow-Off Assembly for 4" and 6" Waterlines
407B	Permanent or Temporary 4" and 6" Blow-Off
407C	Standard 4" and 6" Temporary Fill Point
408	Horizontal Thrust Blocking
409	Vertical Thrust Blocking
410	Standard Straddle Block
411	Standard Gravity Sanitary Sewer Separation
412	Water Project Symbols
413	Standard Valve Box Detail
414	Standard Valve Box Detail for Blow-Off Standpipe
415A	Standard Hersey MCT2 Compound Meter Installation - 3"
415B	Standard Hersey MCT2 Compound Meter Installation - 4" & 6"
415C	Standard Hersey MFM/MCT2 Compound Meter Installation – 4"x2", 6"x3" & 8"x4"
415D	Standard Hersey Compound Meter Installation Notes
416A	Backflow Assembly
416B	Double Check Valve (Detector) Backflow Assembly
416C	Backflow Assembly
416D	Double Check Valve (Detector) Backflow Assembly
416E	Reduced Pressure Backflow Assembly
416F	Backflow Assembly
416G	Reduced Pressure Principle Assembly 3" and Larger
416H	Reduced Pressure Principle Small Assembly 2 ½" and Smaller
417	Example Sump with Sump Pump
418	Tracer Wire Installation
419	Protective Casing for Crossing Cathodically Protected Structures
420	Protective Geomembrane for Crossing Cathodically Protected Structures
421	Standard Wire Connection for Steel and Ductile Iron Pipe
422	Standard Post Type Test Station Detail
423	Standard Post Type Test Station Detail for Casings
424	Standard Post Type Test Station Detail for Insulating Joint
425	Standard Post Type Test Station Detail for Crossings
426	Standard Flush Mounted Test Station
427	Standard Insulating Flange
428	Standard Joint Bond Detail – Push-on and Mechanical Joint
429	Standard Joint Bond Detail – Valve

Drawing Number	Street Work Drawings
500	Local Transitional Street Section
501	Collector Street Section
502	Arterial Street Section

503	Minor Access Street
504	Not used
505	Not used
506	Alley Street Section
507	Not used
508	Standard Cul-de-sac
509	Branch Turnaround
510	Residential Driveway Approach
511	Commercial Driveway Approach
512	Curb Return Driveway Approach
513	Typical Sidewalk Detail
514	Sidewalk Ramp
515	Pedestrian / Bicycle Accessway Detail
516	Bollard Detail
517	Street Barricade
518	Type "C" Curb
519	Monolithic Curb and Gutter
520	Mountable Curb
520A	Mountable Curb - Alternate
521	Mountable Curb Transition Side Inlet Catch Basin
522	Typical Utility Placement Detail
523	Manhole Adjustment Detail
524	14 ft. Wide Mountable Speed Bump
525	22 ft. Wide Speed Hump
526	Standard Monument Box
527	Standard Street Light Detail
528	Not used
529	Mast Arm Detail
530	Not used
531	Standard Signpost
532	Not used
533	Tree Well Detail
534	Paver Crosswalk Detail
535	Concrete Crosswalk Detail
536	Not used
537	Not used
538	Not used

<i>Drawing Number</i>	<i>Storm Drain Drawings</i>
601-A	Catch Basin
601-B	Catch Basin Section and Curb Detail
601-C	Curb Detail at Catch Basin
602	(not used)

603	Frame and Grate
604	Storm Sump System
605	Storm Sump System and Sedimentation Manhole (Typical Retrofit Installation)
605-A	Polypropylene Hanging Ladder
606-A	Inlet-Manhole Standard
606-B	Inlet-Manhole Combination Curb Inlet
606-C	Inlet-Manhole Alternate Top
607	Flow Control Manhole
608	Detention Pipe Typical Closed
609	Ditch Inlet Type D
609-A	Ditch Inlet Frame & Grate
610	CG-2 Double Catch Basin
610-A	CG-2 Double Catch Basin Curb Section
611	CG-2 Frame and Grate

AASHTO HS-20 LOADING AREAS


Size Inches	NON-REINFORCED		REINFORCED		
	C 14 Class 2	C 14 Class 3	C 76 Class III	C 76 Class IV	C 76 Class V
6	20.5	24.5	-----	-----	-----
8	16.0	19.5	-----	-----	-----
10	13.5	16.0	-----	-----	-----
12	11.5	13.5	11.0	15.5	22.5
15	11.5	12.5	11.5	16.0	23.0
18	11.5	12.5	12.0	16.5	23.5
21	10.5	13.0	12.0	17.0	24.5
24	10.5	13.5	12.5	17.5	25.0
27	-----	-----	13.0	17.5	25.5
30	-----	-----	13.0	18.0	25.5
36	-----	-----	14.0	19.0	26.5
42	-----	-----	14.5	19.5	27.0
48	-----	-----	15.0	20.0	28.0
54	-----	-----	15.5	21.0	28.5
60	-----	-----	16.5	21.5	29.0
66	-----	-----	17.0	22.0	30.0
72	-----	-----	18.0	22.5	30.5
78	-----	-----	19.0	23.0	31.0
84	-----	-----	19.5	24.0	31.5
90	-----	-----	20.5	24.5	32.5
96	-----	-----	21.0	25.5	33.0
102	-----	-----	22.0	26.0	33.5
108	-----	-----	22.5	27.0	34.0
114	-----	-----	23.0	28.0	35.0
120	-----	-----	24.0	28.5	35.5

EARTH LOAD ONLY

Size Inches	NON-REINFORCED C 14 Class 2
6	20.5
8	16.0
10	13.5
12	11.5
15	11.5
18	11.5
21	11.5
24	11.5
27	-----
30	-----


NOTES: Depths are for pipes with Class "B" pipe zone.
 Depths are based upon a trench width of TRANSITION width or greater.
 Depths are in feet to the invert of the pipe.
 Pipe must conform to ASTM requirements.
 Loads can be only backfill and AASHTO HS-20.
 Minimum cover over pipe is 3.0 feet.
 Compacted weight of backfill over pipe does not exceed 120 pcf.

DRAWN AJH			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 CONCRETE PIPE ALLOWABLE INSTALLATION DEPTH	SCALE N.T.S.
DIV.				DATE 2002
REV.	DATE	APPR.		APPR.
				DWG. NO. 301




PLAN

MATERIAL TO BE GRAY
CAST IRON ASTM A-48,
CLASS 30.
WEIGHT = 237 LBS.



SECTION "A"-"A"

DRAWN			AJB	<div>COMMUNITY DEVELOPMENT</div> <div>CITY OF SCAPPOOSE</div> <div>34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056</div> <div>INDUSTRIAL MANHOLE FRAME</div> <div>7" DEPTH</div>	SCALE	N.T.S.
DIV.					DATE	2002
REV.	DATE	APPR.			APPR.	
					DWG. NO.	302




MANHOLE INSTALLATION

ALL MATERIAL AND WORK SHALL COMPLY WITH CITY OF SCAPPOOSE STANDARD SPECIFICATIONS.

THE SAND COLLAR SHALL BE FABRICATED BY AN APPROVED MANUFACTURER AND NOT FIELD MADE.

THE NOMINAL PIPE SECTION (DIM. "G") SHALL BE COATED WITH AN EPOXY ADHESIVE COMPATIBLE WITH BOTH PVC AND CONCRETE GROUT AND COARSE AGGREGATE APPLIED.



SECTION THROUGH ADAPTER

SIZE	"A"	"B"	"C"	"D"	"E" *	"F" *	"G"
4"	4.22"	3.97"	4.25"	4.50"	5.20"	2.90"	7.00"
6"	6.28"	5.92"	6.32"	6.68"	7.50"	6.25"	7.00"
8"	8.40"	7.92"	8.46"	8.94"	10.10"	4.10"	7.00"
10"	10.50"	9.90"	10.57"	11.17"	12.40"	4.70"	7.00"
12"	12.50"	11.78"	12.58"	13.30"	14.50"	5.15"	7.00"
15"	15.30"	14.43"	15.36"	14.49"	18.00"	5.95"	7.00"
18"	18.70"	17.63"	18.76"	19.83"	21.98"	5.90"	7.00"
21"	22.05"	20.79"	22.11"	23.37"	25.63"	6.40"	7.00"
24"	24.80"	23.38"	25.04"	26.46"	28.80"	15.75"	7.00"
27"	27.95"	26.35"	28.27"	29.87"	32.50"	18.30"	7.00"
30"					35.00"		7.00"
36"					41.50"		7.00"


* APPROXIMATE DIMENSION

ALL MATERIAL AND WORK SHALL COMPLY WITH CITY OF SCAPPOOSE STANDARD SPECIFICATIONS.

DRAWN: AJH			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 MANHOLE ADAPTER (SAND COLLAR)	SCALE N.T.S.
DIV.				DATE 2002
REV.	DATE	APPR.		APPR.
				DWG. NO. 303


NOTES:

1. COVER AND FRAME TO BE MACHINED FOR TRUE BEARING.
2. MATERIAL SHALL BE GRAY CAST IRON, ASTM A-48, CLASS 30. Wt. = 139 lbs. +/-
3. TWO HOLE LID FOR SANITARY SEWERS.
4. 16 HOLE LID FOR STORM SEWERS.



FOR SANITARY SEWERS ONLY (2) HOLES ARE USED AND SHOWN SHADED.
FOR STORM SEWERS ONLY (16) HOLES ARE USED AND SHOWN OPEN & SHADED.

THESE COVERS TO BE
USED FOR IN-ROAD
LOCATIONS ONLY.



DRAWN			AJH	<div>COMMUNITY DEVELOPMENT</div> <div>CITY OF SCAPPOOSE</div> <div>34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056</div> <div>SANITARY and STORM</div> <div>MANHOLE COVER</div>	SCALE	N.T.S.
DIV.					DATE	2002
REV.	DATE	APPR.			APPR.	
					DWG. NO.	305


NOTES:

1. COVER AND FRAME TO BE MACHINED FOR TRUE BEARING.
2. MATERIAL SHALL BE GRAY CAST IRON, ASTM A-48, CLASS 30. Wt. = 139 lbs. +/-
3. TWO HOLE LID FOR SANITARY SEWERS.
4. 16 HOLE LID FOR STORM SEWERS.

DRILL $5/8"$ ϕ HOLE,
SLOT $5/8"$ THRU.
TYP. (4) PLACES.

COUNTERBORE $1\ 7/16"$ ϕ
 $1/2"$ DEEP.
TYP. (3) PLACES.

$3/4"$ ϕ TOP x
 $1"$ ϕ BOTTOM HOLES.




PLAN

SANITARY MANHOLE HOLES SHOWN SHADED.
SEE DWG. 305 FOR ADDITIONAL NOTES

$1/2"$ ϕ - 13 NC x 1" STAINLESS STEEL
HEX HEAD CAP SCREW W/ $1\ 1/4"$ ϕ OD
x $3/32"$ THK. 8-18 STAINLESS STEEL
WASHER. (3) EA. REQUIRED.

LOCKDOWN DETAIL



SECTION "A"-"A"

DRAWN	AJH	
DIV.		
REV.	DATE	APPR.

COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE

34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056

SANITARY and STORM MANHOLE
TAMPERPROOF COVER

SCALE N.T.S.

DATE 2002

APPR.

DWG. NO. 306


DRILL $0.434" \phi \pm 0.004"$
 1.125" DEEP, TAP $1/2"-13$ NC,
 COUNTERBORE $1\ 7/16" \phi$ $1/2"$ DEEP,
 TYPICAL (3) PLACES.

DRILL $0.457" \phi \pm 0.003"$
 1" DEEP, TAP $1/2"-20$ NF,
 INSTALL LOCATING STUD.

$3/32"$ WIDE x $5/32"$ DEEP SLOT


$1/2" \phi$ 18-8 STAINLESS
 STEEL STOCK THREADED
 $1/2"-20$ NF.

LOCATING STUD



PLAN

MATERIAL TO BE GRAY
 CAST IRON ASTM A-48,
 CLASS 30.
 WEIGHT = 237 LBS.




SECTION "A" - "A"

DRAWN AJB		
DIV.		
REV.	DATE	APPR.

COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE
 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056
SANITARY and STORM TAMPERPROOF
MANHOLE FRAME

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	307


1. COVER AND FRAME TO BE MACHINED FOR TRUE BEARING.
2. MATERIAL SHALL BE GRAY CAST IRON, ASTM A-48, CLASS 30. Wt. = 139 lbs. +/-



DRAWN AJH			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 SANITARY and STORM MANHOLE WATERPROOF COVER	SCALE N.T.S.
DIV.				DATE 2002
REV.	DATE	APPR.		APPR.
				DWG. NO. 308


DRILL $0.434'' \pm 0.004''$
TAP $1/2''-13$ NC, TYPICAL
(3) PLACES.

MACHINE $9/32''$ WIDE x
 $3/16''$ DEEP GROOVE ON
 $23 3/4''$ ID CIRCLE.




PLAN

MATERIAL TO BE GRAY
CAST IRON ASTM A-48,
CLASS 30.
WEIGHT = 237 LBS. \pm



SECTION "A" - "A"


DRAWN			AJH	<div>COMMUNITY DEVELOPMENT</div> <div>CITY OF SCAPPOOSE</div> <div>34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056</div> <div>SANITARY and STORM WATERPROOF</div> <div>MANHOLE FRAME</div>	SCALE	N.T.S.
DIV.					DATE	2002
REV.	DATE	APPR.			APPR.	
					DWG. NO.	309



TYPICAL CONNECTION PLAN FOR 3 OR 4 LOT COMMON LATERAL.
4 LOT PLAN SHOWN, 3 LOT SIMILAR.

PRIVATE EASEMENT ARRANGEMENT SHOWN TO BE USED ONLY WHEN
SEWER IN PUBLIC ROAD RIGHT-OF-WAY CANNOT BE USED.


DRAWN RRB			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 SANITARY SEWER CONNECTION, 3 or 4 LOTS w/ PRIVATE EASEMENTS	SCALE N.T.S.
DIV.				DATE 2002
REV.	DATE	APPR.		APPR.
				DWG. NO. 310



TYPICAL CONNECTION PLAN FOR 5 OR MORE LOTS.
5 LOT PLAN SHOWN, 6 OR MORE LOTS SIMILAR.


PUBLIC EASEMENT ARRANGEMENT SHOWN TO BE USED ONLY WHEN
PUBLIC ROAD RIGHT-OF-WAY ALIGNMENT CANNOT BE USED.

DRAWN RRB			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 SANITARY SEWER CONNECTION, 5 or MORE LOTS /w PUBLIC EASEMENT	SCALE N.T.S.
DIV.				DATE 2002
REV.	DATE	APPR.		APPR.
				DWG. NO. 311



TYPICAL CONNECTION FOR A 2 LOTS W/ COMMON (SIAMESE) SERVICE BRANCH

DRAWN RRB			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 SANITARY SEWER CONNECTION, TWO SINGLE FAMILY LOTS	SCALE N.T.S.
DIV.				DATE 2002
REV.	DATE	APPR.		APPR.
				DWG. NO. 312




TYPICAL CONNECTION FOR SINGLE FAMILY RESIDENCE.

DRAWN RRB			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 SANITARY SEWER CONNECTION, SINGLE FAMILY	SCALE N.T.S.
DIV.				DATE 2002
REV.	DATE	APPR.		APPR.
				DWG. NO. 313

2" x 4" STAKE FROM INVERT TO 1' ABOVE EXISTING GRADE. STAKE SHALL BE CONTINUOUS AND REMAIN VERTICAL AFTER BACKFILLING. END SHALL BE PAINTED WHITE. (TYPICAL AT ALL SERVICES.)

STAMP "S" IN FACE OR TOP OF CURB.



NOTES:

1. SCHEME AND DEPTH FOR HOUSE SERVICE TO BE DETERMINED IN THE FIELD BY ENGINEER.

2. SERVICE SHALL NOT BE BACKFILLED PRIOR TO INSPECTION.


PIPE PAY LENGTH

TRENCH EXCAVATION AND BACKFILL PAY LENGTH

1/8 BEND

MINIMUM SLOPE 1/4" PER FOOT

SERVICE BRANCH WITH RISER



TRENCH EXCAVATION AND BACKFILL PAY LENGTH

PIPE PAY LENGTH

MINIMUM SLOPE 1/4" PER FOOT



1/8 BEND

SERVICE BRANCH WITHOUT RISER

DRAWN			AJB		
DIV.					
REV.		DATE		APPR.	

COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE
34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056
SERVICE BRANCH


SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	314




NOTE:

1. WHERE APPROVED BY THE ENGINEER, GRANULAR TRENCH STABILIZATION SHALL BE PLACED PRIOR TO THE PIPE ZONE MATERIAL. SIZE AND DEPTH OF TRENCH STABILIZATION PER SOIL CONDITIONS.
2. PIPE ZONE MATERIAL SHALL BE COMPACTED TO 90% OF ASTM D1557/ AASHTO T-180.
3. PIPE ZONE MATERIAL SHALL BE COMPACTED AS SPECIFIED PRIOR TO BACKFILLING THE REMAINDER OF THE TRENCH.


DRAWN WRH			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 SANITARY and STORM PIPE ZONE BEDDING and BACKFILL	SCALE N.T.S.
DIV.				DATE 2002
REV.	DATE	APPR.		APPR.
				DWG. NO. 315



FOR 6", 8", & 10" SEWER PIPE
0.29 Cu. Yd. Concrete Min.



FOR 12", & 15" SEWER PIPE
0.37 Cu. Yd. Concrete Min.



FOR 18", 21" & 24" SEWER PIPE
0.42 Cu. Yd. Concrete Min.

NOTES:

ALL MATERIAL AND WORK TO BE IN ACCORDANCE WITH CITY OF SCAPPOOSE PUBLIC WORKS DESIGN STANDARDS.

ALL CONCRETE SHALL BE 3,000 psi 28 DAY COMPRESSIVE STRENGTH, WITH 2" TO 4" SLUMP.

ANCHOR WALLS MUST BE USED WITH PIPES WITH SLOPES OVER 20%.

ANCHOR WALLS TO BE EQUALLY SPACED

PIPE SLOPE	WALL SPACING
20%	21'
100%	12'


PROPORTION SPACING WITH SLOPE. PLACE WALL IMMEDIATELY BELOW BELL OF PIPE WHERE POSSIBLE.

ANCHORS FOR PIPES LARGER THAN 24" TO BE DESIGNED BY GEOTECH. ENG'R.

DRAWN	AJH
DIV.	
REV.	DATE
	APPR.

COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE
34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056
SEWER PIPE
ANCHOR WALL

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	316



VERTICAL SECTION

DIMENSIONS—IN.		BARS REQ'D.
"A"	"B"	
6"	16"	C
8"	19"	C
10"	21"	C
12"	23"	C
15"	26 $\frac{1}{2}$ "	C
18"	30 $\frac{1}{2}$ "	C
21"	39"	C&D
24"	43"	C&D
27"	50"	C&D

NOTES:

ALL MATERIAL AND WORK TO BE IN ACCORDANCE WITH CITY OF SCAPPOOSE STANDARD SPECIFICATIONS AND REQUIREMENTS.

ALL CONCRETE SHALL BE 3,000 PSI, 3" TO 5" SLUMP.

STEEL REINFORCING SHALL BE NO. 5 ϕ IN CONFORMANCE WITH ASTM A 615, GRADE 60, WITH DEFORMATIONS PER ASTM A 305.


DRAWN AJH			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 SEWER PIPE CONCRETE ENCASEMENT	SCALE N.T.S.
DIV.				DATE 2002
REV.	DATE	APPR.		APPR.
				DWG. NO. 317

NOTES:

ALL MATERIAL AND WORK SHALL BE IN COMPLIANCE WITH CITY OF SCAPPOOSE STANDARD SPECIFICATIONS.


SEE STD. DWG. NOS. 319, 323, OR 324 FOR OTHER DIMENSIONS AND NOTES.

THIS DESIGN TO BE USED FOR ALL DROPS 2 FEET AND LESS.



SECTION "A"-"A"

MINIMUM OF 9" WALL BETWEEN PIPES. SEE STANDARD DRAWING 324 FOR ALTERNATIVE.



PARTIAL PLAN

DRAWN AJH		
DIV.		
REV.	DATE	APPR.



COMMUNITY DEVELOPMENT		
CITY OF SCAPPOOSE		
34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056		
SHALLOW INSIDE DROP MANHOLE		

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	318





PLAN

DRAWN			AJB	COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 SHALLOW MANHOLE FOR 27" and LESSER DIA. PIPES	SCALE	N.T.S.
DIV.					DATE	2002
REV.	DATE	APPR.			APPR.	
					DWG. NO.	319




DRAWN			DIV'N.			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 SIAMESE SERVICE BRANCH			SCALE		N.T.S.	
DIV.									DATE:		2002	
REV.		DATE		APPR.					APPR.			
									DWG. NO. 320			



FRAME & COVER


SALEM IRON WKS.
#4233 & 4234 OR EQUAL.

PLAN



ELEVATION

DRAWN			AJB			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE			SCALE		N.T.S.		
DIV.									DATE		2002		
REV.		DATE		APPR.		34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056			APPR.				
						STANDARD CLEANOUT			DWG. NO.			321	




NOTES:

PARTITION MATERIAL SHALL BE 1/2" H.D.P.E (TYP. PER ASSOCIATED PIPE), OR 1/8" FIBERGLASS (TYP. PER PIPE INC.) OR 16 GA. ALUMINUM OR 18 GA. STAINLESS STEEL. FIBERGLASS SHALL BE 3 OR 4 MAT LAYUP PER MANUFACTURERS' RECOMMENDATIONS.


MAXIMUM FLOW IS 3 C.F.S. FOR INSIDE DROP MANHOLE. IF GREATER THAN 3 C.F.S. FLOW USE A OUTSIDE DROP MANHOLE DESIGN.

FOR A 48" DIA. MANHOLE THE MAXIMUM INCOMING PIPE DIAMETER IS 15". A LARGER DIAMETER INCOMING PIPE WILL REQUIRE A SPECIAL DESIGN.

STANDARD TYPE MANHOLE SHOWN. FLATTOP MANHOLE SIMILAR.



1/2"Ø SELF TAPPING CONCRETE ANCHORS, PHILLIPS S-12 OR APPROVED EQUAL, w/ 1/2"Ø x 1 1/2" Lg. STAINLESS STEEL BOLT & STAINLESS STEEL LOCK WASHER.




DETAIL A
(PARTITION ATTACHMENT)

15" MAX. DIA., DUCTILE IRON, CL. 52 PIPE. EXTEND TO UNDISTURBED GROUND. USE FOWLER OR FERNCO COUPLING TO CONNECT TO PVC OR CONCRETE SEWER PIPE.

CLASS "B" PIPE ZONE

IMPORTED SELECT BACKFILL COMPACTED TO 95% M.D.D. PER AASHTO T-180.

REMOVABLE DEFLECTION PLATE (MIN. 12" WIDTH). MATERIAL TO BE STAINLESS STEEL, ALUMINUM, FIBERGLASS OR H.D.P.E. PLATE. TOP PARTITION TO BE CUT SO THAT BOTTOM OF CUT MATCHES THE INVERT OF THE INCOMING PIPE. THE RADIUS OF THE CUT SHOULD MATCH THAT OF THE INSIDE OF THE INCOMING PIPE.



SECTION "C"-"C"

DRAWN	AJH	
DIV.		
REV.	DATE	APPR.

COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE
34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056

STANDARD INSIDE DROP MANHOLE

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	322

MANHOLE FRAME
AND
COVER PER
PLANS/SPECS.

REDUCING TOP SLAB TO BE DESIGNED &
CONSTRUCTED FOR DEPTH AND TRAFFIC
CONDITIONS BY MANUFACTURER. FOR SLABS
WITHIN 1'7" OF STREET, OPENING TO BE 25".

MINIMUM OF 12" PRECAST WALL
BETWEEN PIPE CORING REQ'D.

COLLAR

18" MAX. TO 1st
FLEXIBLE JOINT

0° PIPE DEFLECTION
SHOWN.

PLAN

MINIMUMS


PIPE DIA. IN.	BARREL DIA.* IN.	"A" DIM. IN.	"B" DIM. IN.	"C" DIM. IN.
30"	66"	6"	8"	8"
33"	72"	7"	8"	8"
36"	72"	7"	8"	8"
42"	78"	7"	8"	8"
48"	84"	8"	8"	8"
54"	90"	8"	8"	8"
60"	96"	9"	12"	12"
66"	102"	10"	12"	12"
72"	108"	10"	12"	12"
78"	114"	10"	12"	12"
84"	120"	11"	12"	12"
90"	126"	11"	12"	12"
96"	132"	12"	12"	12"

* APPLIES TO (2) PIPE MANHOLES
WITH 0° DEFLECTION. OTHER
NUMBERS OF PIPES OR DEFLECTION
WILL REQUIRE LARGER SIZE.

NOTES:

ALL MATERIAL & WORK SHALL BE AS
REQUIRED BY CITY OF SCAPPOOSE
STANDARD PLANS & SPECIFICATIONS.

STEPS TO BE AS DETAILED IN
STANDARD SPECIFICATIONS.



VERTICAL SECTION

DESIGN BARREL REINFORCING FOR CONDITIONS.

SLOPE SHELVES 1:12, 18" MINIMUM WIDTH.

CORE MANHOLE WALL 2" MIN., 4" MAX.
CLEAR OF PIPE WALL. GROUT WITH NON-
SHRINK GROUT & POUR 4"x4" CONCRETE
COLLAR AROUND PIPE CONNECTION.

2" MIN. FOR CAST-IN-PLACE BASE

FORM GROUT CHANNEL TO 2/3 DIA. HEIGHT.

REINFORCED PRE-CAST OR CAST-IN-PLACE
BOTTOM SLAB. SUBMIT CALCULATIONS &
DESIGN FOR PRIOR APPROVAL.

12" MINIMUM THICKNESS OF 3/4"-0"
COMPACTED CRUSHED ROCK.

DRAWN: AJH

DIV.

REV.

DATE

APPR.

COMMUNITY DEVELOPMENT

CITY OF SCAPPOOSE

34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056


STANDARD MANHOLE
FOR 30" and LARGER DIA. PIPES

SCALE: N.T.S.


DATE: 2002

APPR.

DWG. NO. 324



SECTION "A"-"A"




NOTES:

ALL MATERIAL AND WORK SHALL BE IN COMPLIANCE WITH CITY OF SCAPPOOSE STANDARD SPECIFICATIONS.

JOINTS SHALL BE WATER TIGHT AND COATED WITH WATERPROOF RUBBERIZED MASTIC MATERIAL BEFORE SETTING RISERS AND TOP. INSIDE JOINTS SHALL BE GROUTED.

MANHOLES SHALL HAVE A 12" MIN., 24" MAX. BOTTOM RISER. RISER TO BE BEDDED IN THE CAST-IN-PLACE CONCRETE AS THE BASE TAKES ITS' INITIAL SET.


DRAWN			AJB	COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 STANDARD SAMPLING MANHOLE	SCALE	N.T.S.
DIV.					DATE	2002
REV.	DATE	APPR.			APPR.	
					DWG. NO.	325



THIS MANHOLE FRAME
MAY BE USED ONLY FOR
LOCAL ROAD LOCATIONS.


PLAN

MATERIAL TO BE GRAY
CAST IRON ASTM A-48,
CLASS 30.
WEIGHT = 172 LBS.



SECTION "A" - "A"


DRAWN AJB			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 SUBURBAN MANHOLE FRAME 3" DEPTH	SCALE N.T.S.
DIV.				DATE 2002
REV.	DATE	APPR.		APPR.
				DWG. NO. 326




NOTES:

1. THE TAP SHALL NOT BE MADE EXCEPT IN THE PRESENCE OF A CITY INSPECTOR; NOR SHALL ANY CONNECTION BE MADE WITHOUT CITY APPROVAL.
2. A "INSERTA-TEE" OR "FERNCO" TYPE TAPPING SADDLE SHALL BE USED.
3. THE HOLE MADE IN MAIN TO BE CORED.
4. C OF TAP TO BE ABOVE SPRINGLINE.
5. 4" MAXIMUM HOLE FOR 8" MAIN (CUT-IN TEE TO BE USED FOR 6" SERVICE BRANCH ON 8" MAIN).
6. 4" SERVICE BRANCH MAY BE USED FOR SINGLE FAMILY LOTS ONLY.


DRAWN			AJB	COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 TAP IN EXISTING SEWER MAIN FOR SERVICE BRANCH	SCALE	N.T.S.
DIV.					DATE	2002
REV.	DATE	APPR.			APPR.	
					DWG. NO.	327



TRAVELED UNIMPROVED STREET



CONCRETE SURFACE STREET




CTB STREET

NOTES:


1. BACKFILL SHALL BE IMPORTED GRANULAR OR NATIVE BACKFILL AS APPROVED.
2. COMPACTION STANDARD SHALL BE ASTM D1557/AASHTO T-180 WHEN NOT OTHERWISE SPECIFIED.
3. PRIOR TO SURFACE RESTORATION SAWCUT EXISTING SURFACING 6" OUTSIDE EXTENT OF DISTURBED SOILS.

* M.D.D. = MAX. DRY DENSITY


DRAWN WRH			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 TYPICAL TRENCH SECTION BACKFILL and SURFACING	SCALE N.T.S.
DIV.				DATE 2002
REV.	DATE	APPR.		APPR.
				DWG. NO. 328



IN OFF-ROAD AREAS



ASPHALT CONCRETE SURFACE STREET



ASPHALT CONCRETE SURFACE STREET & GEOTEXTILE FABRIC


NOTES:

1. BACKFILL SHALL BE IMPORTED GRANULAR OR NATIVE BACKFILL AS APPROVED.
 2. COMPACTION STANDARD SHALL BE ASTM D1557/AASHTO T-180 WHEN NOT OTHERWISE SPECIFIED.
 3. PRIOR TO SURFACE RESTORATION SAWCUT EXISTING SURFACING 6" OUTSIDE EXTENT OF DISTURBED SOILS.
- * M.D.D. = MAX. DRY DENSITY

DRAWN WRH			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 TYPICAL TRENCH SECTION BACKFILL and SURFACING	SCALE N.T.S.
DIV.				DATE 2002
REV.	DATE	APPR.		APPR.
				DWG. NO. 329

NOTES:

1. HYDRANTS TO BE APPROVED BY CITY ENGINEER.
2. HYDRANT COLOR TO BE SHERWIN WILLIAMS GCC-5006.
3. ALL MJ'S ON TEE, VALVE & F.H. TO BE RESTRAINED WITH "MEGALUG" FOLLOWER GLANDS. RESTRAIN MIN 10' OF PIPE EACH SIDE OF TEE ON MAIN LINE. NO JOINTS BETWEEN VALVE AND SHOE UNLESS OVER 18'.
4. HYDRANT DRAIN HOLES TO REMAIN OPEN TO DRAIN ROCK AND OPERATIONAL
5. MIN. 4 CU. FT. OF 1 1/2"-3/4" CLEAN DRAIN ROCK SHALL BE PLACED AROUND SHOE UP TO A MIN. OF 6" ABOVE DRAIN OUTLETS.
6. WHERE PLANTER STRIP EXISTS. HYDRANT SHALL BE PLACED SO FRONT PORT IS A MIN. OF 24" BEHIND FACE OF CURB.
7. WHERE INTEGRAL S/W & CURB EXIST, HYD. PUMPER PORT SHALL BE PLACED AT BACK OF SIDEWALK, OR AS DIRECTED BY ENGINEER.
8. BURY OF HYDRANT SHALL BE MEASURED FROM FINISHED GRADE TO BOTTOM OF CONNECTING PIPE. HYDRANT SHALL HAVE A MAX. OF A 6' BURY.
9. HYDRANT VALVE SHALL BE MUELLER RESILIENT WEDGE GATE VALVE #A-2360-16 OR APPROVED EQUAL.
10. WHERE NO SIDEWALK EXISTS AROUND A HYDRANT, INCLUDING PLANTER STRIPS, PLACE A 5' x 5' x 4" THICK CONC. PAD AROUND HYDRANT.



DRAWN	DRAWN
DIV.	DEPT
REV.	DATE
	APPR.

COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE
 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056
STANDARD FIRE HYDRANT ASSEMBLY

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	401

IF NATIVE MATERIAL IS UNSUITABLE FOR BACKFILL, APPROVED GRANULAR MATERIAL WILL BE REQ'D

NATIVE MATERIAL OR 4" OF 1" MINUS AS REQUIRED.


SAW CUT EXISTING A.C. TO NEAT, STRAIGHT LINES.

3" A.C. PAVEMENT OR SAME AS EXIST. DEPTH, WHICHEVER IS GREATER, OR AS REQ'D BY PERMIT.


T-CUT 1 1/2" THICK OR DEPTH OF EXIST. TOP LIFT, WHICHEVER IS GREATER

EXIST. BASE ROCK

3/4" MINUS CRUSHED AGG. PER CITY SPECS.



SHOULDER OR LANDSCAPED SECTION




PAVING SECTION

NOTES.

1. ALL WATER MAINS SHALL HAVE A MIN. COVER OF 36" IN RIGHT-OF-WAY AND 48" IN EASEMENTS
2. ALL TRENCH BACKFILL SHALL BE COMPACTED TO 95% OF MAX. DENSITY PER AASHTO T-180 OR AS SPECIFIED IN THE CONTRACT DOCUMENTS.
3. ALL TRENCH BACKFILL AND PATCHING SHALL CONFORM TO THE STANDARDS AND SPECIFICATIONS OF THE GOVERNING AGENCY.
4. PAYMENT FOR PAVEMENT CUT AND REPAIR SHALL INCLUDE ALL A.C. AND CRUSHED AGGREGATE TO 12" BELOW FINISH GRADE.
5. SAND BACKFILL WILL BE REQ'D IN PIPE ZONE WHEN PIPE LINE IS TO BE POLYBAGGED.
6. BACKFILL SHALL BE PLACED AND COMPACTED IN LIFTS, OR AS DETERMINED IN FIELD BY THE CITY ENGINEER.

DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 STANDARD TRENCH SECTION	SCALE	N.T.S.
DIV.				DATE	DATE
REV.	DATE	APPR.		APPR.	
				DWG. NO.	402



MATERIALS:

1. OLDCASTLE METER BOX, BODY NO. 37, LID AND COVER NO. 37-S.
2. MUELLER CORP. STOP NO. H-15000 (FLARE), H-15008 (110 COMPRESSION), OR FORD F600 (FLARE).
3. 1" SOFT TEMPER, TYPE "K" COPPER TUBING COMPLYING WITH ASTM B-88.
4. MUELLER ANGLE METER STOP NO. H-14255 (FLARE), H-14258 (110 COMPRESSION), OR FORD NO. KV23-444W (FLARE).


NOTES:

1. SUBSTITUTES FOR ANY MATERIALS SHOWN SHALL BE APPROVED BY THE CITY ENGINEER.
2. ALL PIPE AND STRUCTURE ZONES SHALL BE BACKFILLED USING 3/4" MINUS CRUSHED AGG. AND COMPACTED TO 95% MAX. DENS. AS DETERMINED BY AASHTO T-180.
3. WHEN AN ACTIVE CATHODIC PROTECTED SYSTEM IS ENCOUNTERED, SCH. 40 PVC SHALL BE INSTALLED WITH IMPERVIOUS PLUG AS SHOWN ABOVE.
4. METER BOX SHALL BE CENTERED OVER THE COMPLETED METER ASSEMBLY.
5. FOR VACANT RESIDENTIAL LOTS, LOCATE SERVICE 18" INSIDE SIDE LOT LINE. LOT LINE TO BE PROJECTED PERPENDICULAR TO CURB.
6. ANGLE METER STOP SHALL BE PERPENDICULAR TO CURB LINE.
7. SET CORP. STOP WITH OPERATING NUT AT 3 OR 9 O'CLOCK.
8. TRAFFIC BEARING METER BOX LIDS SHALL BE USED WHERE METERS ARE LOCATED WITHIN ANY PORTION OF DRIVEWAY OR APRON AND OTHER TRAFFIC AREAS.
9. ONLY APPROVED BIT AND TAPPING MACHINE ALLOWED FOR INSTALLATION OF CORP. STOP.
10. COPPER SERVICE SHALL BE INSTALLED IN A DIRECT LINE BETWEEN TAP AND METER.

DRAWN		DRAWN	
DIV.		DEPT	
REV.	DATE	APPR.	

COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE
 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056
STANDARD 1" SERVICE

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	403



MATERIALS:

1. "VANCOUVER" VALVE BOX, LID & 6" PVC EXTENSION (SEE STANDARD DETAIL. NO. 413)
2. PIPE O.D. x 2" TEE OR 2" F.I.P. SERVICE SADDLE (A.Y. McDONALD MFG. CO. MODEL 3826 OR APPROVED EQUAL)
3. 2" BRASS M.I.P. NIPPLE
4. 2" F.I.P. GATE VALVE (MUELLER NO. A-2369-8 OR APPROVED EQUAL)
5. 2" M.I.P. x COP. FLARE (MUELLER NO. H-15425, FORD NO. C28-77) OR MUELLER 110 COMPRESSION COUPLING (NO. H-15428)
6. 2" ASTM B-88 TYPE "K" RIGID COPPER TUBING. SOFT TEMPER REQ'D WITH FLARE FITTINGS.
7. 2" 90° BEND, COP. FLARE (MUELLER NO. H-15525 OR FORD NO. L22-77) OR MUELLER 110 COMPRESSION (NO. H-15526)
8. 1 1/2" - 2" ANGLE METER STOP, MUELLER NO. H-14276 (FLARE) OR H-14277 (110 COMPRESSION) OR FORD NO. FV23-777W (FLARE)
9. OLDCASTLE METER BOX, BODY NO. 38 (1 1/2"), LID & COVER NO. 38-S (1 1/2"), OR 65-DPRL (2")

NOTES:

1. SUBSTITUTES FOR ANY MATERIALS SHOWN SHALL BE APPROVED BY THE CITY ENGINEER.
2. ALL PIPE AND STRUCTURE ZONES SHALL BE BACKFILLED USING 3/4" MINUS CRUSHED AGG. AND COMPACTED TO 95% MAX. DENSITY AS DETERMINED BY AASHTO T-180.
3. WHEN AN ACTIVE CATHODIC PROTECTION SYSTEM IS ENCOUNTERED, SCH. 40 PVC SHALL BE INSTALLED WITH AN IMPERVIOUS PLUG, AS SHOWN.
4. METER BOX SHALL BE CENTERED OVER THE COMPLETED METER AND FITTING ASSEMBLY.
5. CUSTOMER SHALL INSTALL AN APPROVED BACKFLOW PREVENTION ASSEMBLY AT RIGHT-OF-WAY.
6. ANGLE METER STOP SHALL BE PERPENDICULAR TO CURB LINE.

DRAWN	DRAWN	
DIV.	DEPT	
REV.	DATE	APPR.

COMMUNITY DEVELOPMENT		
CITY OF SCAPPOOSE		
34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056		
STANDARD 2" SERVICE		
IRRIGATION (1-1/2"-2" METER)		

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	404A



SEE STANDARD DETAIL DRAWING NO. 404C
FOR MATERIAL AND INSTALLATION NOTES



MATERIALS:

1. "VANCOUVER" VALVE BOX, LID & 6" PVC EXTENSION (SEE STANDARD DETAIL NO. 413)
2. PIPE O.D. x 2" TEE OR 2" F.I.P. SERVICE SADDLE (A.Y. McDONALD MFG. CO. MODEL3826 OR APPROVED EQUAL)
3. 2" BRASS M.I.P. NIPPLE
4. 2" F.I.P. GATE VALVE (MUELLER NO. A-2369-8 OR APPROVED EQUAL)
5. 2" M.I.P. x COP. FLARE (MUELLER NO. H-15425, FORD NO. C28-77) OR MUELLER 110 COMPRESSION COUPLING (NO. H-15428)
6. 2" ASTM B-88 TYPE "K" RIGID COPPER TUBING. SOFT TEMPER REQ'D WITH FLARE FITTINGS.
7. 2" 90° BEND, COP. FLARE (MUELLER NO. 525 OR FORD NO. L22-77) OR MUELLER 110 COMPRESSION (NO. H-15526)
8. OLDCASTLE METER BOX, BODY NO. 38 (1 1/2"), OR 65 (2"), LID & COVER NO. 38-S (1 1/2"), OR 65-DPRL (2")
9. 2" 90° BEND, COMP. x M.I.P. (MUELLER H-15531)
10. 2" METER YOKE (SETTER) (MUELLER NO. B-2423-99000)
11. 2" COMP. x F.I.P. (MUELLER H-15451) W/PVC PLUG

NOTES:

1. SUBSTITUTES FOR ANY MATERIALS SHOWN SHALL BE APPROVED BY THE CITY ENGINEER.
2. ALL PIPE AND STRUCTURE ZONES SHALL BE BACKFILLED USING 3/4" MINUS CRUSHED AGG. AND COMPACTED TO 95% MAX. DENSITY AS DETERMINED BY AASHTO T-180.
3. WHEN AN ACTIVE CATHODIC PROTECTION SYSTEM IS ENCOUNTERED, SCH. 40 PVC SHALL BE INSTALLED WITH AN IMPERVIOUS PLUG, AS SHOWN.
4. METER BOX SHALL BE CENTERED OVER THE COMPLETED METER AND FITTING ASSEMBLY.
5. CUSTOMER SHALL INSTALL AN APPROVED BACKFLOW PREVENTION ASSEMBLY AT RIGHT-OF-WAY.
6. METER SETTER SHALL BE PERPENDICULAR TO CURB LINE.

DRAWN		DRAWN		COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 STANDARD 2" SERVICE-- DOMESTIC WITH OR W/O IRRIGATION (1-1/2"-2" METER)	SCALE	N.T.S.
DIV.		DEPT			DATE	2002
REV.	DATE	APPR.			APPR.	
					DWG. NO.	404C



MATERIALS

1. ECLIPSE NO. 88 SAMPLING STATION WITH THREADED OUTLET NOZZLE AND BRASS STANDPIPE (KUPFERLE FOUNDRY).
2. 3/4" TYPE 'K' SOFT TEMPER COPPER TUBING.
3. 3/4" MIP x COP. FLARE 1/4 BEND, MUELLER H-15530 (FLARE), H-15531 (110 COMPRESSION), OR FORD L28-33 (FLARE).
4. 3/4" FIP BALL VALVE, MUELLER (110 COMPRESSION) B-25209, OR FORD B22-333W (FLARE).
5. 3/4" CORP. STOP, MUELLER H-15000 (FLARE), H-15008 (110 COMPRESSION), OR FORD F600 (FLARE).
6. STD. 'VANCOUVER' VALVE BOX.
7. CONCRETE PAD 4" THK., 46" LG BY 31" WIDE
8. PAINT TOP WITH SHERWIN WILLIAMS GCC-5033 (BLUE).
9. PAINT BASE WITH SHERWIN WILLIAMS INDUSTRIAL ENAMEL PURE WHITE.

NOTES

1. ALL PIPE AND STRUCTURES SHALL BE BACKFILLED WITH 3/4"-0" CRUSHED ROCK COMPACTED TO MIN. 95% OF MAX. DENSITY PER AASHTO T-180.
2. SET STATION AT LOT LINE.
3. WHEN CROSSING CATHODICALLY PROTECTED SYSTEM, INSTALL PVC SLEEVE PER STD. DETAIL 403.

DRAWN	DRAWN
DIV.	DEPT
REV.	DATE
	APPR.


COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE
 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056
STANDARD WATER SAMPLING STATION

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	405

DRAWN		DRAWN	
DIV.		DEPT	
REV.	DATE	APPR.	

COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056			
STANDARD COMBINATION AIR VALVE UNIT			

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	406



MATERIALS:

1. A.Y. McDONALD MDL3826 OR APROVED EQUAL
2. 2" M.I.P. CORP. STOP
3. 2" ASTM B-88 RIGID COPPER
4. 2" BRASS 1/4 BEND
(FLARE x FLARE OR MUELLER 110 CTS)
5. 12"x12"x4" CONCRETE BLOCK
6. 2" BRASS 1/4 BEND (F.I.P. x FLARE),
OR (F.I.P. x MUELLER 110 COMPRESSION)
7. 2" R.W. F.I.P. GATE VALVE
8. 2" x 3" BRASS M.I.P. NIPPLE
9. 2" COMBINATION AIR VALVE
(VAL-MATIC #202C OR APCO #145C-2)
10. 2" x 1 1/2" BRASS M.I.P. NIPPLE
11. 2" F.I.P. BRASS 1/4 BEND
12. STD. 48" CONCRETE MANHOLE CONE
13. VALLEY IRON & STEEL FRAME #106, 108 OR
APPD. EQUAL.
14. VALLEY IRON & STEEL FRAME #105, 107 OR
APPD. EQUAL.
15. 3/4" MINUS CRUSHED AGG.
16. 1 1/2" - 3/4" CLEAN DRAIN ROCK
17. 2" BRASS COUPLING (M.I.P. x FLARE OR MUELLER
110 COMPRESSION)

18. 2" M.I.P. BRASS 1/4 BEND WITH SCREEN
ON OUTLET

19. 3 EA. CONCRETE BLOCKS

20. 2" UNION (FLARE OR MUELLER 110 COMPRESSION)

21. "HOT BOX" (EZBOX #EZ75)

22. "VANTCOUVER" STYLE VALVE BOX. SEE STANDARD
DETAIL DRAWING 413.


NOTES:

1. INSTALLATION LOCATED AT HIGH POINT OF MAIN.
2. 48" MANHOLE BARREL SECTIONS SHALL BE USED TO
INCREASE DEPTH IF NECESSARY.
3. ALL PIPE AND STRUCTURE ZONES SHALL BE COMPACTED
TO 95% OF MAX. DENSITY AS DETERMINED BY AASHTO
T-180 OR AS SPECIFIED IN THE CONTRACT DOCUMENTS.
4. DETAIL NOT FOR SHALLOW INSTALLATIONS. INSTALLATIONS
FOR WATERLINES WITH LESS THAN 36" OF COVER SHALL
BE INDIVIDUALLY DESIGNED BY THE ENGINEER.
5. GROUT ALL AREAS WHERE COPPER PASSES THROUGH
MANHOLE CONE
6. PLACE "HOT BOX" AT BACK OF SIDEWALK IN UTILITY
EASEMENT OR OBTAIN 5' x 5' WATER FACILITY EASEMENT.


DRAWN		DRAWN		COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 STANDARD 2" BLOW-OFF ASSEMBLY FOR 4" AND 6" WATERLINES	SCALE	N.T.S.
DIV.		DEPT			DATE	2002
REV.	DATE	APPR.			APPR.	
					DWG. NO.	407A

1. BACKFILL WITH SELECT CRUSHED AGGREGATE A MINIMUM OF 6" ON ALL SIDES.
2. ON TEMPORARY BLOW-OFFS ONLY, AN MJ CAP TAPPED 4" OR 6" MAY BE SUBSTITUTED FOR REDUCER.
3. TEMPORARY BLOW-OFF IS ONE REMOVED AT THE END OF PROJECT CONSTRUCTION. A PERMANENT BLOW-OFF REMAINS ON THE PROJECT AFTER ACCEPTANCE.
4. PLACE BLOW-OFF STANDPIPE 3 FT. INSIDE P/L. LINE AT END OF STREET (2 FT. FROM BARRICADE).
5. USE "VANCOUVER" STYLE VALVE BOX, LID, AND 6" PVC EXTENSION FOR BLOW-OFF VALVE. USE "PORTLAND" STYLE VALVE BOX, LID, AND 8" PVC EXTENSION FOR BLOW-OFF STAND PIPE (SEE DETAILS 413 & 414)

BLOW-OFF SIZES REQUIRED	
MAIN SIZE	BLOW-OFF SIZE
4" TO 6"	2"
8" TO 12"	4"
14" TO 18"	6"
20" & UP	PER ENGR.



DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 PERMANENT OR TEMPORARY 4" AND 6" BLOW-OFF	SCALE	N.T.S.
DIV.				DATE	2002
DEPT				APPR.	
REV.	DATE	APPR.		DWG. NO.	407B



NOTES:

1. ALL FILLING, FLUSHING, AND TESTING OF NEW WATERLINE FACILITIES SHALL BE DONE THROUGH A 6" DOUBLE CHECK ASSEMBLY WITH A METERING DEVICE.
2. PROVIDE TEMPORARY BLOCKING AS REQUIRED.
3. ALL PIPING AND FITTINGS SHALL BE GALVANIZED IRON.
4. FOR 8"—12" WATERLINES: FILL POINT SHALL BE 4" PIPING AND FITTINGS. FOR 14"—18" WATERLINES: FILL POINT SHALL BE 6" PIPING AND FITTINGS. FOR 20" AND LARGER: FILL POINT SHALL SIZED AS DETERMINED BY THE ENGINEER.


DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 STANDARD 4" AND 6" TEMPORARY FILL POINT	SCALE	N.T.S.
DIV.				DATE	2002
DEPT				APPR.	
REV.	DATE	APPR.		DWG. NO.	407C

FITTING SIZE (Inches)	TEE,& WYE ①	STRADDLE BLOCK ②	90° BEND ③ PLUGGED CROSS TEE PLUGGED—RUNS	45° BEND ④	22 1/2° BEND ④	11 1/4° BEND ④
2	*	*	*	*	*	*
4	1.7	2.1	2.4	1.3	*	*
6	3.7	4.9	5.3	2.9	1.5	*
8	6.7	8.7	9.5	5.1	2.7	1.3
10	10.5	13.6	14.8	8	4.1	2
12	15.1	19.6	21.3	11.6	5.9	2.9
16	26.8	34.8	37.9	20.5	10.4	5.2
18	33.9	44	47.9	25.9	12.8	6.7
LARGER	* *	* *	* *	* *	* *	* *
BEARING AREA OF THRUST BLOCKS (sq. ft.)						

- ALL VALUES ARE BASED ON THE FOLLOWING ASSUMPTIONS:
AVG. PRESSURE = 100 PSI x 2 (safety factor); 1500 PSF SOIL BEARING CAPACITY; NORMAL DISTRIBUTION DESIGN VELOCITY NOT TO EXCEED 5 F/S.
- ALL FITTINGS SHALL BE WRAPPED IN PLASTIC PRIOR TO PLACEMENT OF CONCRETE.
- ALL THRUST BLOCKS SHALL BE FORMED TO ELIMINATE ANY CONCRETE AROUND FITTING BOLTS.
- BEARING SURFACE OF THRUST BLOCKING SHALL BE AGAINST UNDISTURBED SOIL.
- ALL CONCRETE MIX SHALL HAVE A MIN. 28 DAY STRENGTH OF 3000 PSI.
- ALL PIPE ZONES SHALL BE GRAVEL FILLED AND COMPACTED.
- THRUST BLOCKS FOR PLUGGED CROSS AND PLUGGED TEE SHALL HAVE #4 REBAR LIFTING LOOPS INSTALLED AS SHOWN.
- VERTICAL THRUST DETAILS – SEE DWG. #409
- STRADDLE BLOCK DETAILS – SEE DWG. #410.

* BLOCK TO UNDISTURBED TRENCH WALLS


* * THRUST BLOCKS FOR PIPES LARGER THAN 18" WILL BE INDIVIDUALLY DESIGNED BY THE ENGINEER.




DRAWN			DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056			SCALE N.T.S.	
DIV.			DEPT						DATE 2002	
REV.	DATE	APPR.	HORIZONTAL THRUST BLOCKING						APPR.	
									DWG. NO. 408	

NOTES:

1. GRAVITY VERTICAL THRUST BLOCKS VALUES SHALL BE REVIEWED BY THE ENGINEER.
2. KEEP CONCRETE CLEAR OF JOINT AND JOINT ACCESSORIES. FITTINGS SHALL BE WRAPPED IN PLASTIC PRIOR TO PLACEMENT OF CONCRETE.
3. CONCRETE THRUST BLOCKING SHALL BE POURED AGAINST UNDISTURBED EARTH.
4. CONCRETE MIX SHALL HAVE A MIN. 28 DAY STRENGTH OF 3000 P.S.I.
5. GRAVITY THRUST BLOCK VOLUMES FOR VERTICAL BENDS HAVING UPWARD RESULTANT THRUSTS ARE BASED ON TEST PRESSURE OF 150 P.S.I.G. AND THE WEIGHT OF CONCRETE = 4050 LBS./CU.YD.
6. VERTICAL BENDS THAT REQUIRE A GRAVITY THRUST BLOCK VOLUME EXCEEDING 5 CUBIC YARDS REQUIRE SPECIAL BLOCKING DETAILS DESIGNED BY THE ENGINEER. NOTE VOLUMNS SHOWN INSIDE HEAVY LINE IN TABLE.
7. PAYMENT SHALL BE THE SAME AS FOR HORIZONTAL THRUST BLOCKS.
8. ALL REBAR SHALL BE GALVANIZED IN ACCORDANCE WITH ASTM-123 (MIN. 3.4 MIL). REBAR SHALL BE BENT BEFORE GALVANIZATION, AND LAST 4" OF BAR SHALL BE BENT 90 DEGREES WITH A 1/2" RADIUS BEND. REBAR SHALL BE TIGHTLY FIT TO RESTRAINED FITTING.
9. FOR HORIZONTAL THRUST BLOCK DETAILS SEE DETAIL NO. 408.



GRAVITY VERTICAL THRUST BLOCK



NORMAL VERTICAL
THRUST BLOCK


VOLUME OF GRAVITY THRUST BLOCK IN CUBIC YARDS (VERTICAL BENDS)			
FITTING SIZE	BEND ANGLE		
	45 °	22 1/2°	11 1/4 °
4	1.1	0.4	0.2
6	2.7	1.0	0.4
8	4.0	1.5	0.6
10	6.0	2.3	0.9
12	8.5	3.2	1.3
14	11.5	4.3	1.8
16	14.8	5.6	2.3

FITTING SIZE	ROD SIZE	EMBED- MENT
12" AND LESS	#6	30"
14" - 16"	#8	36"


DRAWN	DRAWN	
DIV.	DEPT	
REV.	DATE	APPR.

COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE
 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056
VERTICAL THRUST BLOCKING

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	409



TOP VIEW



FRONT VIEW

MATERIALS:

1. CONCRETE STRADDLE BLOCK.
2. 2-EBAA IRON "MEGALUG" FOLLOWER GLANDS
3. #4 REBAR EACH WAY, 12" O/C.
4. NO JOINTS ALLOWED BETWEEN STRADDLE BLOCK AND FITTING/BLOW-OFF ASSEMBLY.
5. FITTING/BLOW-OFF ASSEMBLY


NOTES:

1. STRADDLE BLOCKS HEIGHT AND WIDTH SHALL BE DESIGNED INDIVIDUALLY BY THE ENGINEER AND SHALL BE BASED ON THE FOLLOWING:
 - a.) 200 PSI WATER PRESSURE
 - b.) SOIL BRG. CAPACITY
 - c.) STEEL SIZE AND SPACING
2. BEARING AREA OF BLOCK SHALL BE AGAINST UNDISTURBED SOIL.
3. STRADDLE BLOCK SHALL HAVE A MINIMUM OF 18" COVER.
4. CONCRETE SHALL HAVE A MIN. 28-DAY STRENGTH OF 3000 PSI
5. ALL FITTINGS, & PIPE WITHIN THE CONC. SHALL BE WRAPPED IN 8 MIL. PLASTIC
6. STRADDLE BLOCK HEIGHT (H) & WIDTH (W) SHALL BE DETERMINED BY THE ENGINEER.

DRAWN	DRAWN
DIV.	DEPT
REV.	DATE
	APPR.

COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE
 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056
STANDARD STRADDLE BLOCK

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	410



ZONE 1: ONLY CROSSING RESTRICTIONS APPLY

ZONE 2: CASE-BY CASE DETERMINATION

ZONE 3: PARALLEL WATERLINE PROHIBITED

ZONE 4: PARALLEL WATERLINE PROHIBITED

NOTES:

1. WHERE THE PROPOSED WATERLINE WILL BE INSTALLED PARALLEL TO AN EXISTING GRAVITY SANITARY SEWER MAIN OR LATERAL LINE, THE SEPERATION BETWEEN THE TWO SHALL BE AS INDICATED ABOVE.
2. CROSSING:
 - a. WHENEVER POSSIBLE, THE BOTTOM OF THE WATERLINE SHALL BE 1.5 FEET ABOVE THE TOP OF THE SEWER LINE. ONE FULL LENGTH OF WATERLINE SHALL BE CENTERED AT THE CROSSING, REGARDLESS OF VERTICAL SEPERATION.
 - b. WHERE IT IS NOT POSSIBLE FOR THE WATER LINE TO BE 1.5 FEET ABOVE THE SEWER LINE, OR THE WATERLINE PASSES UNDER THE SEWER LINE, THE EXISTING SEWER LINE SHALL BE EXPOSED FOR A DISTANCE OF 10 FEET ON EACH SIDE OF THE CROSSING, AND SHALL BE REPLACED WITH C-900 PVC, DR-18, DR-25 OR CLASS 50 DUCTILE IRON PIPE AS APPROVED BY THE ENGINEER, AND A LENGTH OF WATER PIPE SHALL BE CENTERED AT THE CROSSING, OR AS APPROVED BY THE ENGINEER.
3. SEPERATION FROM FORCE MAIN SANITARY SEWER SHALL BE REVIEWED ON A CASE-BY-CASE BASIS

DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 STANDARD GRAVITY SANITARY SEWER SEPERATION	SCALE	N.T.S.
DIV. DEPT				DATE	2002
REV.	DATE	APPR.		APPR.	
				DWG. NO.	411

LEGEND

EXISTING

	FIRE HYDRANT
	GATE VALVE
	BUTTERFLY VALVE W/Oper.
	WATER METER
	WATER MAIN
	THRUST BLOCK
	MJ PLUG ON TEE
	UNDERGROUND TV CABLE
	UNDERGROUND POWER
	UNDERGROUND TELEPHONE
	GAS MAIN W/VALVE
	POWER POLE W/GUY
	CULVERT
	MANHOLE
	SANITARY SEWER
	STORM DRAIN
	SURVEY MONUMENT
	DITCH OR STREAM



PROPOSED

	FIRE HYDRANT
	GATE VALVE
	BUTTERFLY VALVE W/Oper.
	WATER METER
	WATER MAIN
	THRUST BLOCK
	STRADDLE BLOCK
	BLOW-OFF
	SAMPLE STATION

JOINTS and FITTINGS

	FLANGE JOINT (FLG)
	MECHANICAL JOINT
	BELL END OF PIPE
	FLANGED TEE
	45 DEGREE BEND, MJ
	ADAPTER, FLG x MJ
	REDUCER, FLG
	MJ PLUG ON TEE
	MJ CAP
	BLIND FLANGE ON TEE
	SLEEVE OR COUPLING
	MECHANICAL JOINT W/"MEGALUG"
	RESTRAINED BELL JOINT


DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 WATER PROJECT SYMBOLS	SCALE	N.T.S.
DIV.				DATE	2002
REV.	DATE	APPR.		APPR.	
				DWG. NO.	412



NOTES:


1. VALVE BOXES SHALL BE CENTERED DIRECTLY OVER THE VALVE NUT IN A VERTICAL POSITION.
2. VALVE BOX TOP SHALL BE ADJUSTED TO MEET FINISHED GRADE.
3. PVC SHALL BE ON CONTINUOUS PIECE – NO BELLS OR COUPLERS.
4. USE FOR ALL VALVES AND 2" BLOW-OFF STANDPIPES

DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 STANDARD VALVE BOX DETAIL			SCALE N.T.S.	
DIV. DEPT						DATE 2002	
REV.	DATE	APPR.				APPR.	
						DWG. NO. 413	



1. VALVE BOXES SHALL BE CENTERED DIRECTLY OVER THE STANDPIPE IN A VERTICAL POSITION.
2. VALVE BOX TOP SHALL BE ADJUSTED TO MEET FINISHED GRADE.
3. PVC SHALL BE ON CONTINUOUS PIECE-NO BELLS OR COUPLERS.
4. USE FOR 4" & 6" BLOW-OFF STANDPIPES AND FLUSH MOUNTED CATHODIC PROTECTION TEST STATIONS ONLY.

DRAWN		DRAWN		COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 STANDARD VALVE BOX DETAIL FOR BLOW-OFF STANDPIPE	SCALE	N.T.S.
DIV.		DEPT			DATE	2002
REV.	DATE	APPR.			APPR.	
					DWG. NO.	414




METER	3"
INCOMING LINE SIZE	4"
BY-PASS LINE SIZE	4"
UTILITY VAULT NO./LID NO.	687-LA/ 687-TL2-332P
A	24" MIN
B	36" MIN
C	6"MIN -12"MAX
D	24" MIN
E	24" MIN

FITTINGS & VALVES BY CONTRACTOR

- (A) 4" FLG TEE
- (B) 4" MJ x FLG ADAPTER
- (C) 4" MJ 90° BEND
- (D) 4" MJ x FLG R.W. GATE VALVE
- (E) 4" FLG. R.W. GATE VALVE
- (F) 4" FLG. x P.E. CONTINUOUS D.I. PIPE

FITTINGS, VALVES & METER BY CITY

- (1) 4" x 3" FLG. REDUCER
- (2) 4" x 3" MJ x FLG R.W. GATE VALVE
- (3) 3" HERSEY/MCT 2 COMPOUND METER



MECHANICAL JOINT WITH MEGALUG RETAINER GLAND


PIPE BELL WITH "FIELD-LOK" TYPE GASKET

ALL FITTINGS, VALVES AND PIPING SHALL BE INSTALLED LEVEL

DRAWN	DRAWN
DIV.	DEPT
REV.	DATE
	APPR.

COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE
 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056
STANDARD HERSEY MCT2
COMPOUND METER INSTALLATION - 3"

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	415A



METER	4"	6"
INCOMING LINE SIZE	4"	6"
BY-PASS LINE SIZE	4"	6"
UTILITY VAULT NO./LID NO.	687-LA/ 687-TL2-332P	5106-LA/ 5106-TL2-332P
A	24" MIN	24" MIN
B	36" MIN	36" MIN
C	6" MIN 12" MAX	6" MIN 12" MAX
D	24" MIN	24" MIN
E	24" MIN	24" MIN


FITTING & VALVES BY CONTRACTOR

- (A) 4" OR 6" FLG TEE
- (B) 4" OR 6" MJ x FLG ADAPTER
- (C) 4" OR 6" 90° BEND
- (D) 4" OR 6" MJ x FLG RW GATE VALVE
- (E) 4" OR 6" FLG RW GATE VALVE
- (F) 4" OR 6" FLG x P.E. CONTINUOUS D.I. PIPE

FITTING, VALVE, & METER BY CITY

- (1) 4" OR 6" MJ x FLG RW GATE VALVE
- (2) 4" OR 6" HERSEY MCT2 COMPOUND METER

DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE			SCALE N.T.S.	
DIV. DEPT						DATE 2002	
REV.	DATE	APPR.	34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056			APPR.	
						STANDARD HERSEY MCT2 COMPOUND METER INSTALLATION - 4" & 6"	



METER	4"x 2"	6"x 3"	8"x 4"
INCOMING LINE SIZE	6"	8"	10"
BY-PASS LINE SIZE	4"	4"	6"
UTILITY VAULT NO./LID NO.	810-LA/ 810-TL2-332P	712-LA/ 712-TL2-332P	816-LA/ 816-TL2-332P
A	24" MIN	24" MIN	24" MIN
B	36" MIN	36" MIN	36" MIN
C	6" MIN 12" MAX	6" MIN 12" MAX	6" MIN 12" MAX
D	24" MIN	24" MIN	26" MIN
E	24" MIN	28" MIN	30" MIN

FITTINGS & VALVES BY CONTRACTOR

4"x2"	6"x3"	8"x4"
(A) 6"x4" FLG TEE	8"x 4" FLG TEE	10"x6" FLG TEE
(B) 6" MJxFLG ADAPTER	8" MJxFLG ADAPTER	10" MJ x FLG ADAPTER
(C) 4" MJ 90° BEND	4" MJ 90° BEND	6" MJ 90° BEND
(D) 6" MJxFLG RW GATE VALVE	8" MJxFLG RW GATE VALVE	10" MJxFLG RW GATE VALVE
(E) 6" FLG RW GATE VALVE	8" FLG RW GATE VALVE	10" FLG RW GATE VALVE
(F) 4" MJxFLG RW GATE VALVE	4" MJxFLG RW GATE VALVE	6" MJxFLG RW GATE VALVE
(G) 6" FLG x PE CONTINUOUS D.I. PIPE	8" FLG x PE CONTINUOUS D.I. PIPE	10" FLG x PE CONTINUOUS D.I. PIPE

FITTINGS, VALVES, & METER BY CITY

4"x2"	6"x3"	8"x4"
(1) 6"x 4" FLG REDUCER	8"x 6" FLG REDUCER	10" x 8" FLG REDUCER
(2) 6" MJxFLG RW GATE VALVE	8" MJxFLG RW GATE VALVE	10" MJxFLG RW GATE VALVE
(3) 4"x 2" HERSEY MFM/MCT2 COMPOUND METER	6"x 3" HERSEY MFM/MCT2 COMPOUND METER	8"x 4" HERSEY MFM/MCT2 COMPOUND METER

DRAWN			DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 STANDARD HERSEY MFM/MCT2 COMPOUND METER INSTALLATION- 4" X 2", 6" X 3", & 8" X 4"			SCALE N.T.S.	
DIV.			DEPT						DATE 2002	
REV.	DATE	APPR.	APPR.							
			DWG. NO. 415C							

NOTES:

1. METER AND DOWNSTREAM VALVE TO BE INSTALLED BY THE CITY ONCE NEW PIPING AND FITTINGS HAVE BEEN TESTED AND ACCEPTED.
2. ALL VAULT WALL OPENINGS SHALL BE CORE DRILLED AND SEALED WITH LINK-SEAL BRAND PIPE SEAL OR APPROVED EQUAL.
3. TOP OF VAULT SHALL BE A MINIMUM OF 12" ABOVE FINISHED GRADE.
4. INSTALL 4" DRAIN FROM BOTTOM OF VAULT FLOOR TO DAYLIGHT, TO BACKFLOW ASSEMBLY VAULT, TO STORM DRAIN SYSTEM OR TO APPROVED SUMP WITH SUMP PUMP. IN NO CASE SHALL BACKFLOW ASSEMBLY VAULT DRAIN INTO METER VAULT.
5. INSTALL 4" BACKWATER VALVE, MDL. NO. 7022 AND SMITH 4" FLOOR DRAIN MDL. NO. 2210 OR APPROVED EQUAL ON FLOOR DRAIN.
6. VAULT SHALL BE CLEAN, DRY AND FREE OF DEBRIS PRIOR TO METER INSTALLATION
7. ALL MECHANICAL JOINTS SHALL BE RESTRAINED WITH "MEGALUG" RETAINER GLANDS.
8. SERVICE LINE INTO VAULT SHALL BE MECHANICALLY RESTRAINED FROM MAINLINE THROUGH VAULT.
9. ALL PIPING TO BE BACKFILL AS DESCRIBED & SHOWN IN STANDARD DETAIL DRAWING 402.
10. INSTALL A MIN. OF 3 PIPE SUPPORTS IN VAULT (GRINNELL NO. 264, ELCEN NO. 50 OR APPROVED EQUAL).
11. ALL PIPING AND FITTINGS IN VAULT SHALL BE LEVEL AND A MINIMUM OF 12" AND A MAX. OF 48" ABOVE THE FLOOR OF VAULT.
12. ONLY APPROVED RESILIENT WEDGE VALVES ARE ALLOWED.
13. ALL VAULT LIDS SHALL BE EQUIPPED WITH 2 CAST IRON METER LID OPENINGS. ALL DOORS SHALL BE TL2-332P.
14. VAULT SHALL BE EQUIPPED WITH AN OSHA APPROVED LADDER. IF VAULT DEPTH IS GREATER THAN 6', AN OSHA APPROVED EXTENSION LADDER SHALL BE INSTALLED.
15. PIPE BETWEEN THE TWO TEES SHALL BE ONE LEVEL CONTINUOUS PIECE.
16. ALL FITTINGS, VALVES AND PIPING THROUGH ENTIRE VAULT SHALL BE LEVEL AT COMPLETION OF INSTALLATION.
17. VAULT SHALL BE SEALED WITH "CRYSTAL SEAL" AT MANUFACTURER.

DRAWN		DRAWN		COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 STANDARD HERSEY COMPOUND METER INSTALLATION NOTES	SCALE	N.T.S.
DIV.		DEPT			DATE	2002
REV.	DATE	APPR.			APPR.	
					DWG. NO.	415D

CITY OF SCAPPOOSE CROSS CONNECTION PROGRAM

BACKFLOW ASSEMBLY AND VAULT INSTALLATION STANDARDS

- * DOUBLE CHECK VALVE ASSEMBLY
- * DOUBLE CHECK DETECTOR ASSEMBLY
- * REDUCED PRESSURE (R.P.) ASSEMBLY



CONTACTS

<u>DEPARTMENT</u>	<u>NAME</u>	<u>PHONE NO.</u>
CITY ENGINEER	EUGENE SMITH	503-543-7184
FIELD SERVICES	TERRY ANDREWS	503-543-7184
BUILDING OFFICIAL	DON SALLEE	503-543-7184
FIRE DEPARTMENT	MIKE GREISEN	503-543-5026

DRAWN		DRAWN		COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 BACKFLOW ASSEMBLY	SCALE	N.T.S.
DIV.		DEPT			DATE	2002
REV.	DATE	APPR.			APPR.	
					DWG. NO.	416A

NO OTHER DEVICES
SHALL BE CONNECTED
TO THE DCVA OR DCDA.

LOCAL FIRE DEPT.
AND PLUMBING CODE
REQUIREMENTS APPLY
TO ALL WATER
FACILITIES PAST THE
BACKFLOW VAULT.

DOOR LOCATION

LINK-SEAL

OREGON STATE
HEALTH DEPT.
APPROVED ASSEMBLY & INSTALLATION

CITY OF
SCAPPOOSE
STANDARDS

24" MIN.

FLANGE
COUPLING
ADAPTOR (TYP.)

12" MIN.

6" MIN.

FLOW

GATE
VALVE

PROPERTY
LINE

TOP VIEW
NTS

3 GALVANIZED OR EPOXY
COATED "STAND-ON"
PIPE SUPPORTS

6' MIN.

6" MIN.

6" MIN.

12" MIN.

SIDE VIEW
NTS

4" DRAIN TO DAYLIGHT OR
SUMP PUMP & HIGH WATER ALARM TO DAYLIGHT AS
APPROVED BY CITY

DRAWN		DRAWN	
DIV.		DEPT	
REV.	DATE	APPR.	

COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE
34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056
DOUBLE CHECK VALVE (DETECTOR)
BACKFLOW ASSEMBLY

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	416B

CITY OF SCAPPOOSE
REQUIREMENTS FOR BACKFLOW PREVENTION ASSEMBLY
INSTALLATIONS ON 1 1/2" AND LARGER DOMESTIC SERVICES,
IRRIGATION SERVICES AND FIRELINE SERVICES

AN APPROVED BACKFLOW PREVENTION ASSEMBLY IS REQUIRED ON ALL 1 1/2" AND LARGER DOMESTIC METER SIZE SERVICES, PLUS ALL DEDICATED IRRIGATION AND ALL FIRELINE SYSTEMS. AN ASSEMBLY WILL BE APPROVED BY THE CITY OF SCAPPOOSE ONLY IF THE STATE OF OREGON HEALTH DIVISION HAS APPROVED ITS USE AS A BLACKFLOW ASSEMBLY, AND THE ASSEMBLY IS TESTABLE. THE ASSEMBLY SHALL BE INSTALLED AT THE PROPERTY LINE. WHEN IT IS NOT POSSIBLE TO LOCATE THE ASSEMBLY AT THE PROPERTY LINE, THE PROPOSED LOCATION MUST BE APPROVED BY THE FIELD SERVICES SUPERVISOR BEFORE INSTALLATION. A WATER SERVICE SHALL NOT BE TURNED ON UNTIL ALL REQUIRED BACKFLOW PREVENTION ASSEMBLIES ARE INSTALLED, INSPECTED, TESTED, AND REGISTERED WITH THE CITY OF SCAPPOOSE (SEE NOTE 8 BELOW). COST OF ALL INSTALLATIONS, INCLUDING ALL COST OF INITIAL INSPECTION AND TESTING FEES, SHALL BE THE RESPONSIBILITY OF THE CUSTOMER. THE COSTOMER WILL BE RESPONSIBLE FOR ALL MAINTENANCE AND TESTING OF THE ASSEMBLY AND VAULT WHEN USED.

CONSTRUCTION AND DESIGN STANDARDS FOR WATER FACILITIES

1. ALL PIPE WILL BE INSTALLED TO THE CITY OF SCAPPOOSE PUBLIC WORKS STANDARDS.
2. THE CITY OF SCAPPOOSE WILL BE FURNISHED WITH THREE SETS OF PLANS AND SPECIFICATIONS. THE PLANS WILL BE DRAWN AT A SCALE OF 1"=20' FOR PLAN CHECK. ONE SET OF REVISED PLANS WILL BE RETURNED TO THE ENGINEER FOR REVISIONS.
3. THE CONTRACTOR WILL KEEP ONE SET OF APPROVED PLANS AT THE CONSTRUCTION SITE.
4. THE ENGINEER WILL FURNISH THE CITY OF SCAPPOOSE 48-HOUR NOTICE PRIOR TO CONSTRUCTION.
5. WATER FACILITIES WILL BE INSTALLED IN THE PRESENCE OF THE CITY OF SCAPPOOSE INSPECTOR. THE INSPECTOR SHALL HAVE ACCESS TO THE CONSTRUCTION SITE AT ALL TIMES.
6. NEW MAINS ARE TO BE PRESSURE TESTED AND DISINFECTED BY THE CONTRACTOR AND PROVEN TO BE BACTERIOLOGICALLY SAFE PRIOR TO PLACING NEW MAINS IN SERVICE AND PRIOR TO CONNECTION TO CITY FACILITIES.
7. UPON COMPLETION OF THE WATER FACILITY, THE ENGINEER WILL NOTIFY THE CITY OF SCAPPOOSE 48 HOURS IN ADVANCE OF DESIRED, FINAL INSPECTION.
8. CONTRACTOR MUST COORDINATE BACKFLOW ASSEMBLY TEST WITH THE FIELD SERVICES SUPERVISOR. (TELEPHONE NO. 503-543-7184) TO RECEIVE SERVICE TO PROPERTY. METER STOPS AND VALVES TO REMAIN LOCKED & OFF UNTIL THAT TIME OF COORDINATION AND APPROVED TEST.

DRAWN		DRAWN		COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVENUE, PO BOX "P", CITY OF SCAPPOOSE, OR. 97056 BACKFLOW ASSEMBLY	SCALE	N.T.S.
DIV.		DEPT			DATE	2002
REV.	DATE	APPR.			APPR.	
					DWG. NO.	416C

DOUBLE CHECK VALVE (DETECTOR) ASSEMBLY
BACKFLOW ASSEMBLY INSTALLATION STANDARD

TO ENSURE PROPER OPERATION AND ACCESSIBILITY OF ALL BACKFLOW PREVENTION ASSEMBLIES, THE FOLLOWING REQUIREMENTS SHALL APPLY TO INSTALLATION OF THESE ASSEMBLIES UNLESS SPECIFICALLY APPROVED BY THE FIELD SERVICES SUPERVISOR. THE CITY OF SCAPPOOSE PUBLIC WORKS STANDARDS AND CHAPTER 5 OF THE CITY CODE WILL TAKE PRECEDENCE IN DESIGN AND INSTALLATION.

1. NO PART OF THE BACKFLOW PREVENTION ASSEMBLY SHALL BE SUBMERGED IN WATER OR INSTALLED IN A LOCATION SUBJECT TO FLOODING. IF INSTALLED IN A VAULT OR CHAMBER, ADEQUATE DRAINAGE SHALL BE PROVIDED ONTO OWNER'S PROPERTY BY EITHER DRAINAGE TO DAYLIGHT OR BY SUMP PUMP TO DAYLIGHT WITH HIGH WATER ALARM SYSTEM. TEST COCKS SHALL BE PLUGGED. THE PLUGS SHALL NOT BE OF DISSIMILAR METALS.
2. THE ASSEMBLY MUST BE PROTECTED FROM FREEZING AND OTHER SEVERE WEATHER CONDITIONS.
3. ONLY ASSEMBLIES APPROVED FOR VERTICAL INSTALLATION MAY BE INSTALLED VERTICALLY.
4. THE ASSEMBLY SHALL BE READILY ACCESSIBLE WITH ADEQUATE ROOM FOR MAINTENANCE AND TESTING. ASSEMBLIES 2 INCHES AND SMALLER SHALL HAVE AT LEAST A 12-INCH CLEARANCE BELOW AND ON BOTH SIDES OF THE ASSEMBLY; AND IF LOCATED IN A VAULT, THE TOP OF THE ASSEMBLY SHALL BE BETWEEN 18 AND 24 INCHES BELOW GRADE.

ALL ASSEMBLIES LARGER THAN 2 INCHES SHALL HAVE A 12-INCH CLEARANCE ON THE BACKSIDE, A 24-INCH CLEARANCE ON THE TEST-COCK SIDE, AND 12 INCH BELOW THE ASSEMBLY. ADEQUATE CLEARANCE (3 INCHES MIN.) MUST BE MAINTAINED ABOVE O.S. & Y. GATE-VALVE STEM. HEADROOM OF 6'-0" IS REQ'D IN VAULTS. ACCESS TO THE ASSEMBLIES AND TO ANY VAULT OR CHAMBER SHALL REMAIN CLEAR AT ALL TIMES. AN OR/OSHA APPROVED CHAMBER LADDER THAT EXTENDS 3 FT. ABOVE SURFACE OF VAULT SHALL BE INSTALLED.

5. NO POST INDICATING VALVES ARE ALLOWED TO BE INSTALLED DIRECTLY ON DOUBLE CHECK DETECTOR ASSEMBLIES.
6. ONLY APPROVED DOUBLE CHECK DETECTOR ASSEMBLIES ARE TO BE USED FOR SYSTEM CONTAINMENT ON FIRE LINE SERVICES IN THE CITY OF SCAPPOOSE THE METER ON BYPASS ASSEMBLY SHALL READ IN CUBIC FEET.
7. IF A FIRE LINE FLOW, OR TAMPER SWITCH IS INSTALLED, IT MUST BE CONNECTED TO A MONITORED FIRE DETECTION SYSTEM APPROVED BY THE FIRE MARSHAL. NO INSTALLATION WILL MODIFY THE BACKFLOW ASSEMBLY OR INTERFERE WITH ITS OPERATION OR MAINTENANCE.
8. ALL BACKFLOW ASSEMBLIES SHALL BE INSTALLED AT THE SERVICE CONNECTION TO THE PREMISES PER OREGON ADMINISTRATIVE RULES 333-61-070, CROSS CONNECTION CONTROL REQUIREMENTS, UNLESS SPECIFICALLY APPROVED BY THE FIELD SERVICES SUPERVISOR. (SERVICE CONNECTION - A LOCATION WHERE THE PUBLIC WATER FACILITIES END AT OR NEAR THE PROPERTY LINE)
9. ALL PIPE BETWEEN MAIN AND ASSEMBLY SHALL BE RESTRAINED. USE "MEGALUG" RETAINER GLANDS ON MJ FITTINGS AND "FIELD-LOK" TYPE GASKETS ON BELL JOINTS. UNI-FLANGE ADAPTERS MAY BE USED IN VAULTS.
10. APPROVED BACKFLOW ASSEMBLY MAY NOT BE MODIFIED IN ANY WAY FROM WHICH IT WAS MANUFACTURED, TESTED AND APPROVED.

DRAWN		DRAWN		COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON DOUBLE CHECK VALVE (DETECTOR) BACKFLOW ASSEMBLY	SCALE	N.T.S.
DIV.		DEPT			DATE	2002
REV.	DATE	APPR.			APPR.	
					DWG. NO.	416D

REDUCED PRESSURE (R.P.) PRINCIPLE BACKFLOW PREVENTION ASSEMBLY (R.P.)

INSTALLATION STANDARD

AS WELL AS IN THE PREVIOUSLY STATED INSTALLATION STANDARDS, THESE INSTALLATION STANDARDS SHALL APPLY TO THE INSTALLATION OF R.P. ASSEMBLIES:

R.P.'S SHALL BE UTILIZED AT PREMISES WHERE A SUBSTANCE IS HANDLED THAT WOULD BE HAZARDOUS TO HEALTH IF INTRODUCED INTO THE POTABLE WATER SYSTEM. THE R.P. IS NORMALLY USED IN LOCATIONS WHERE AN AIR GAP IS IMPRACTICAL. THE R.P. IS EFFECTIVE AGAINST BOTH BACKSIPHONAGE AND BACKPRESSURE.

1. R.P.'S MUST BE SIZED TO PROVIDE AN ADEQUATE SUPPLY OF WATER AND PRESSURE FOR THE PREMISES BEING SERVED. FLOW CHARACTERISTICS ARE NOT STANDARD. CONSULT MANUFACTURER'S SPECIFICATIONS FOR SPECIFIC PERFORMANCE DATA.
2. PREMISES WHERE INTERURPTION OF WATER SUPPLY IS CRITICAL SHOULD BE PROVIDED WITH TWO ASSEMBLIES INSTALLED IN PARALLEL. THEY SHOULD BE SIZED IN SUCH A MANNER THAT EITHER ASSEMBLY WILL PROVIDE THE MINIMUM WATER REQUIREMENTS WHILE THE TWO TOGETHER WILL PROVIDE THE MAXIMUM FLOW REQUIRED.
3. BYPASS LINES ARE PROHIBITED. PIPE FITTINGS WHICH COULD BE USED FOR CONNECTING A BYPASS LINE SHALL NOT BE INSTALLED.
4. THE ASSEMBLY SHALL BE READILY ACCESSIBLE FOR TESTING AND MAINTENANCE AND SHALL BE LOCATED IN AN AREA WHERE WATER DAMAGE TO BUILDING OR FURNISHINGS WOULD NOT OCCURE FROM RELIEF VALVE DISCHARGE. AN APPROVED AIR GAP FUNNEL ASSEMBLY MAY BE USED TO DIRECT MINOR DISCHARGES AWAY FROM THE ASSEMBLY; THIS ASSEMBLY WILL NOT CONTROL FLOW IN A CONTINUOUS RELIEF SITUATION. DRAIN LINES TO ACCOMMODATE FULL RELIEF VALVE DISCHARGE FLOW SHALL BE REQUIRED.

R.P.'S SHALL BE INSTALLED ABOVE GRADE IN WELL DRAINED AREA, BUT MAY BE INSTALLED BELOW GRADE BY APPROVAL OF FIELD SERVICES SUPERVISOR BEFORE INSTALLATION, IF AN ADEQUATE DRAIN BY GRAVITY THROUGH A "BORSIGHT" DRAIN TO DAYLIGHT IS PROVIDED.

ENCLOSURES SHALL BE DESIGNED FOR READY ACCESS AND SIZED TO ALLOW FOR THE MINIMUM CLEARANCES ESTABLISHED BELOW. REMOVABLE PROTECTIVE ENCLOSURES ARE TYPICALLY INSTALLED ON THE SMALLER ASSEMBLIES. BORE SIGHTED DAYLIGHT DRAIN PORTS MUST BE PROVIDED TO ACCOMODATE FULL PRESSURE DISCHARGE FROM THE ASSEMBLY.

ALL ASSEMBLIES LARGER THAN 2 INCHES SHALL HAVE A MINIMUM OF 12 INCHES CLEARANCE ON THE BACK SIDE, 24 INCHES CLEARANCE ON THE TEST COCK SIDE, AND RELIEF VALVE OPENING SHALL BE AT LEAST 12 INCHES PLUS NOMINAL SIZE OF ASSEMBLY ABOVE THE FLOOR OR HIGH TEST POSSIBLE WATER LEVEL WHICHEVER IS HIGHER. HEADROOM OF 6 FEET IS REQUIRED IN VAULTS. A MINIMUM ACCESS OPENING OF 36"x72" INCHES SQUARE IS REQUIRED ON ALL VAULT LIDS. A LADDER MEETING OSHA REQUIREMENTS SHALL BE PERMANENTLY INSTALLED IN THE VAULT, UNLESS A SIDE ENTRY ENCLOSURE IS USED.

DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE		SCALE	N.T.S.
DIV.					DATE	2002
REV.	DATE	APPR.	34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON		APPR.	
					DWG. NO.	416E
			REDUCED PRESSURE BACKFLOW ASSEMBLY			

REDUCED PRESSURE (R.P.) PRINCIPLE BACKFLOW PREVENTION ASSEMBLY (R.P.) INSTALLATION STANDARD



ASSEMBLIES INSTALLED MORE THAN 5 FEET ABOVE FLOOR LEVEL MUST HAVE A SUITABLE PLATFORM FOR USE BY TESTING OR MAINTENANCE PERSONNEL.

5. THE ASSEMBLY MUST BE PROTECTED FROM FREEZING AND OTHER SEVERE WEATHER CONDITIONS.
6. VERTICAL INSTALLATION IS PROHIBITED.
7. THE PROPERTY OWNER ASSUMES ALL RESPONSIBILITY FOR LEAKS AND DAMAGE. THE OWNER SHALL ALSO KEEP THE VAULT REASONABLY FREE OF SILT AND DEBRIS.
8. VARIANCES FROM THESE REGULATIONS WILL BE EVALUTED ON A CASE-BY-CASE BASIS. ANY DEVIATIONS MUST HAVE PRIOR WRITTEN APPROVAL OF THE WATER DIVISION MANAGER PRIOR TO INSTALLATION.

VAULT SIZING CHART FOR DOUBLE CHECK & R.P. BACKFLOW ASSEMBLIES

SIZE	UTILITY VAULT FOR BACKFLOW ASSEMBLY	
	VAULT	LID
3"	577-LA	LID 577-TL2-332P
4"	577-LA	LID 577-TL2-332P
6"	676-LA	LID 676-TL2-332P
8"	687-LA	LID 687-TL2-332P
10"	5106-LA	LID 5106-TL2-332P

DRAWN	DRAWN	COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON BACKFLOW ASSEMBLY	SCALE	N.T.S.
DIV.	DEPT		DATE	2002
REV.	DATE		APPR.	
				DWG. NO.



DRAWN	DRAWN	
DIV.	DEPT	
REV.	DATE	APPR.

COMMUNITY DEVELOPMENT


CITY OF SCAPPOOSE

34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON

REDUCED PRESSURE PRINCIPLE

ALLEMBLY 3" AND LARGER

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	416G



DRAWN		DRAWN	
DIV.		DEPT	
REV.	DATE	APPR.	

**COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE**

34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON


**REDUCED PRESSURE PRINCIPLE
SMALL ASSEMBLY 2-1/2" AND SMALLER**

SCALE N.T.S.

DATE 2002

APPR.

DWG. NO. 416H




NOTES:

1. THIS DETAIL TO BE USED AS A GUIDELINE. SITE SPECIFIC DESIGN SHALL BE COMPLETED BY ENGINEER.
2. SUMP AND SUMP PUMP ASSEMBLY SHALL BE OWNED & MAINTAINED BY THE PROPERTY OWNER BEING SERVED.
3. HIGH WATER ALARM SYSTEM REQUIRED TO MONITOR OPERATION OF SUMP PUMP.

DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON EXAMPLE SUMP WITH SUMP PUMP	SCALE	N.T.S.	
DIV.				DEPT	DATE	2002
REV.	DATE	APPR.		APPR.		
				DWG. NO.	417	

MATERIALS:

- ① 12-GAUGE STRANDED COPPER WIRE WITH BLUE PLASTIC INSULATION
- ② 2" PVC CONDUIT WITH COPPER WIRE INSIDE
- ③ Oldcastle NO. 37 BOX & LID
- ④ CARSONITE BLUE PLASTIC MODEL CUM-375 WITH LABEL CW-112



NOTES:

1. CONDUIT WITH 1 FT RADIUS SWEEPS AT BENDS + 30" OF COVER
2. COIL ENDS OF WIRES IN BOX, ALLOWING 2 FT. FREE WIRE AT END
3. EVERY 400 FEET BRING WIRE TO SURFACE. SEE PARAGRAPH 403.18 OF WATER TECHNICAL REQUIREMENTS SPECS.

DRAWN		DRAWN	
DIV.		DEPT	
REV.	DATE	APPR.	

COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE

34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON


TRACER WIRE INSTALLATION

SCALE N.T.S.



DATE 2002

APPR.


DWG. NO. 418



DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE			SCALE N.T.S.	
DIV. DEPT						DATE 2002	
REV.	DATE	APPR.	34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON			APPR.	
			PROTECTIVE CASING FOR CROSSING CATHODICALLY PROTECTED STRUCTURES			DWG. NO. 419	




DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON PROTECTIVE GEOMEMBRANE FOR CROSSING CATHODICALLY PROTECTED STRUCTURES		SCALE	N.T.S.
DIV.					DATE	2002
REV.	DATE	APPR.			APPR.	
					DWG. NO.	420




NOTES:

1. COPPER SLEEVE REQUIRED FOR EXOTHERMIC WELDING OF #10 AWG AND SMALLER WIRE.
2. USE COPPER SLEEVE ON #2 AWG JOINT BONDING WIRES
3. WELDER AND CARTRIDGE SIZE VARIES ACCORDING TO WIRE SIZE AND PIPE MATERIAL. CONSULT WELDER MANUFACTURER FOR RECOMMENDED WELDER AND CARTRIDGE.
4. APPLY WELD CAP DIRECTLY TO PIPE—NOT TO PIPE WRAP. USE PRIMER IF REQ'D BY MFR. COMPLETELY ENCIRCLE WIRE WITHIN ELASTOMER.
5. REPLAIR ANY DAMAGED COATING NOT COVERED BY WELD CAP ACCORDING TO COATING MFR'S. RECOMMENDATIONS.
6. COVER EXOTHERMIC WELD WITH "GRAY PAD" AS MANUFACTURED BY TAPECOAT.


DRAWN			<div>COMMUNITY DEVELOPMENT</div> <div>CITY OF SCAPPOOSE</div> <div>34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON</div> <div>STANDARD WIRE CONNECTION FOR STEEL AND DUCTILE IRON PIPE</div>	SCALE	N.T.S.
DIV. DEPT				DATE	2002
REV.	DATE	APPR.		APPR.	
				DWG. NO.	421



DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE			SCALE N.T.S.	
DIV. DEPT						DATE 2002	
REV.	DATE	APPR.	34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON			APPR.	
			STANDARD POST TYPE TEST STATION DETAIL			DWG. NO. 422	



DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON STANDARD POST TYPE TEST STATION FOR CASTINGS			SCALE N.T.S.	
DIV.						DATE 2002	
DEPT						APPR.	
REV.						DWG. NO. 423	
DATE							
APPR.							



DRAWN		DRAWN	
DIV.		DEPT	
REV.	DATE	APPR.	

**COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE**


34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON

**STANDARD POST TYPE TEST
STATION DETAIL FOR INSULATING JOINT**

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	424




DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON STANDARD POST TYPE TEST STATION DETAIL FOR CROSSINGS	SCALE	N.T.S.
DIV.				DATE	2002
DEPT				APPR.	
REV.	DATE	APPR.		DWG. NO.	425



DRAWN	DRAWN
DIV.	DEPT
REV.	DATE
	APPR.

COMMUNITY DEVELOPMENT	
CITY OF SCAPPOOSE	
34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON	
STANDARD FLUSH MOUNTED	
TEST STATION	


SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	426




NOTES:

1. ABOVE GRADE INSULATING FLANGE INSTALLATION AS SHOWN.
2. FOR BURIED OR SUBMERGED INSULATION FLANGE INSTALLATION DO NOT INSTALL INSULATING WASHER ON PROTECTED OR NEW SIDE OF FLANGE.
3. COAT BURIED OR SUBMERGED INSULATED FLANGES WITH SPRAY ON UNDERCOATING AFTER ASSEMBLING JOINT AND WRAP WITH A BUTYL RUBBER ADHESIVE, POLYETHYLENE BACKED TAPE.

DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON STANDARD INSULATING FLANGE		SCALE	N.T.S.
DIV.					DATE	2002
REV.	DATE	APPR.			APPR.	
					DWG. NO. 427	




PUSH-ON JOINT BOND



MECHANICAL JOINT BOND

DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON STANDARD JOINT BOND DETAIL— PUSH-ON AND MECHANICAL JOINT			SCALE N.T.S.	
DIV. DEPT						DATE 2002	
REV.	DATE	APPR.				APPR.	
						DWG. NO. 428	



NOTES:


1. ALL WIRE INSULATION IS
HMWPE
2. A NO. 2 A.W.G. STRANDED CABLE
MAY BE SUBSTITUTED FOR THE
NO. 4 A.W.G. STRANDED CABLE.

JOINT BOND—VALVE AND SOLID SLEEVE

DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE			SCALE		N.T.S.	
DIV.						DEPT		DATE	
REV.	DATE	APPR.	34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON			APPR.			
			STANDARD JOINT BOND DETAIL— VALVE			DWG. NO.		429	

TYPICAL STREET SECTION

LOCAL STREETS GREATER THAN 400 FT.



1. ASPHALTIC CONCRETE 1 STAGE CONST. (2 LIFTS) 1 1/2" CLASS "C" ON 1 1/2" CLASS "B".
2 STAGE CONST. (2 LIFTS) 1 1/2" CLASS "C" ON 2 1/2" CLASS "B".
2. AGGREGATE BASE - 1"-0" CRUSHED ROCK, 8" DEPTH.
3. SUBGRADE AND BASEROCK SHALL BE COMPACTED TO 95% RELATIVE DENSITY PER AASHTO T-180.
4. ALTERNATIVE PAVEMENT MATERIALS WILL BE CONSIDERED FOR APPROVAL BY MANAGER.
5. SIDEWALKS IN COMMERCIAL, INDUSTRIAL, AND HILLSIDE CONSTRAINT DISTRICT SHALL ABUT THE CURB. * SIDEWALK WIDTH IN COMMERCIAL/INDUSTRIAL AREA SHALL BE 6' IN WIDTH.
6. WHERE NO PLANTER STRIP IS REQUIRED, THE SIDEWALK SHALL HAVE A MINIMUM 5' CLEAR OF ALL OBSTACLES, UNLESS APPROVED BY CITY ENGINEER.
7. LOCAL STREETS PROJECTED TO HAVE AN AVERAGE DAILY TRAFFIC (ADT) OVER 1000 VEHICLES PER DAY SHALL BE CONSTRUCTED TO A NEIGHBORHOOD COLLECTOR STANDARD.
8. FIRE HYDRANTS BEHIND THE WALK ON HILLSIDE CONSTRAINT DISTRICT AND COMMERCIAL/INDUSTRIAL DISTRICTS REQUIRE A 5FT. BY 5FT. EASEMENT.

STREET AND RIGHT-OF-WAY WIDTHS


FUNCTIONAL CLASSIFICATION	RIGHT-OF-WAY	A PAVEMENT WIDTH	B SIDEWALK WIDTH	C PLANTER STRIP WIDTH
LOCAL STREET	54'	16'	5'	N/A
LS SLOPE HAZARD AREA	40'	14'	5' *	N/A
LS COMMERCIAL INDUSTRIAL DISTRICT	54'	20'	6' *	N/A

DRAWN	MRM
DIV.	TRANSPORTATION
REV.	DATE
	APPR.

COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE
 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON
LOCAL TRANSITIONAL STREET SECTION

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	500

TYPICAL STREET SECTION




1. A PAVEMENT DESIGN TO ACCOMMODATE ANTICIPATED TRAFFIC LOADINGS AND EXISTING SOIL CONDITIONS SHALL BE SUBMITTED TO THE CITY ENGINEER FOR APPROVAL.
2. SUBGRADE AND BASEROCK SHALL BE COMPACTED TO 95% RELATIVE DENSITY PER AASHTO T-180.
3. TYPICAL STRUCTURAL SECTION SHALL CONSIST OF ASPHALTIC CONCRETE ON CRUSHED ROCK. BASE ALTERNATIVE MATERIALS WILL BE CONSIDERED FOR APPROVAL BY CITY ENGINEER.
4. SIDEWALK IN RESIDENTIAL AREAS SHALL BE 5' IN WIDTH AND LOCATED SIX INCHES OFF RIGHT-OF-WAY LINE WITH A PLANTER STRIP.
5. SIDEWALK IN COMMERCIAL AND INDUSTRIAL AREAS SHALL BE 6' IN WIDTH AND SHALL ABUT THE CURB.
6. THE SIDEWALK SHALL HAVE A MINIMUM 5' CLEAR OF ALL OBSTACLES, UNLESS APPROVED BY CITY ENGINEER.
7. COLLECTORS IN COMMERCIAL AND INDUSTRIAL AREAS SHALL HAVE A PAVEMENT WIDTH OF 44'.
8. NEIGHBORHOOD COLLECTORS IN COMMERCIAL AND INDUSTRIAL AREAS SHALL HAVE A RIGHT-OF-WAY WIDTH OF 60' AND A PAVEMENT WIDTH OF 40'.

STREET AND RIGHT-OF-WAY WIDTHS

FUNCTIONAL CLASSIFICATION	RIGHT-OF-WAY	A PAVEMENT WIDTH	B SIDEWALK WIDTH	C PLANTER STRIP WIDTH
MAJOR COLLECTOR	66'	22'	6'	N/A
NEIGHBORHOOD COLLECTOR IN COMMERCIAL OR INDUSTRIAL AREA	60'	18'	6'	NA

DRAWN			MRM			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON			SCALE		N.T.S.	
DIV.			TRANSPORTATION						DATE		2002	
REV.	DATE	APPR.				COLLECTOR STREET SECTION			APPR.			
									DWG. NO.		501	

TYPICAL STREET SECTION



1. A PAVEMENT DESIGN TO ACCOMMODATE ANTICIPATED TRAFFIC LOADINGS AND EXISTING SOIL CONDITIONS SHALL BE SUBMITTED TO THE CITY ENGINEER FOR APPROVAL.
2. SUBGRADE AND BASEROCK SHALL BE COMPACTED TO 95% RELATIVE DENSITY PER AASHTO T-180.
3. ALTERNATIVE PAVEMENT MATERIALS WILL BE CONSIDERED FOR APPROVAL BY CITY ENGINEER.
4. SIDEWALKS SHALL ABUT THE CURB.
5. THE SIDEWALK SHALL HAVE A MINIMUM 5' CLEAR OF ALL OBSTACLES, UNLESS APPROVED BY CITY ENGINEER.


STREET AND RIGHT-OF-WAY WIDTHS

FUNCTIONAL CLASSIFICATION	RIGHT-OF-WAY	A PAVEMENT WIDTH	B SIDEWALK WIDTH	C PLANTER STRIP WIDTH
MAJOR ARTERIAL	100'	37'	6'	6'
MINOR ARTERIAL	72'	22'	6'	6'

DRAWN MRM			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON ARTERIAL STREET SECTION	SCALE N.T.S.
DIV. TRANSPORTATION				DATE 2002
REV.	DATE	APPR.		APPR.
				DWG. NO. 502

TYPICAL STREET SECTION


MINOR ACCESS STREET LESS THAN 150 FT.




1. ASPHALTIC CONCRETE 1 STAGE CONST.(2 LIFTS)1 1/2" CLASS "C" ON 1 1/2" CLASS "B".
2 STAGE CONST.(2 LIFTS)1 1/2" CLASS "C" ON 2 1/2" CLASS "B".
2. AGGREGATE BASE - 1"-0" CRUSHED ROCK, 8" DEPTH.
3. SUBGRADE AND BASEROCK SHALL BE COMPACTED TO 95% RELATIVE DENSITY PER AASHTO T-180.
4. ALTERNATIVE PAVEMENT MATERIALS WILL BE CONSIDERED FOR APPROVAL BY MANAGER.
5. THE MAXIMUM LENGTH OF A MINOR ACCESS STREET SHALL BE 150'.
6. PUBLIC PARKING FOR VISITORS (3-4 SPACES) AND A BRANCH TYPE TURNAROUND SHALL BE PROVIDED AT THE END OF THE MINOR ACCESS STREET. (SEE DETAIL # 509)
7. A "DEAD END" SIGN SHALL BE POSTED AT THE ENTRANCE TO THE MINOR ACCESS STREET.
8. "NO PARKING" SHALL BE POSTED FOR THE ENTIRE LENGTH OF THE MINOR ACCESS STREET.
9. THERE IS NO REQUIREMENT FOR A SIDEWALK OR PLANTER STRIP.

DRAWN M.R.M.			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON MINOR ACCESS STREET	SCALE N.T.S.
DIV. TRANSPORTATION				DATE 2002
REV.	DATE	APPR.		APPR.
				DWG. NO. 503

TYPICAL STREET SECTION



VALLEY CURB DETAIL




1. ASPHALTIC CONCRETE 1 STAGE CONST.(2 LIFTS) 1 1/2" CLASS "C" ON 1 1/2" CLASS "B".
2 STAGE CONST.(2 LIFTS) 1 1/2" CLASS "C" ON 2 1/2" CLASS "B".
2. AGGREGATE BASE - 1'-0" CRUSHED ROCK, 8" DEPTH.
3. SUBGRADE AND BASEROCK SHALL BE COMPACTED TO 95% RELATIVE DENSITY PER AASHTO T-180.
4. ALTERNATIVE PAVEMENT MATERIALS WILL BE CONSIDERED FOR APPROVAL BY MANAGER.
5. PCC CURB OR VALLEY GUTTER SHALL BE 3000 PSI AT 28 DAYS.
6. "NO PARKING" SHALL BE POSTED THE ENTIRE LENGTH OF ALLEY IN RESIDENTIAL AND COMMERCIAL/INDUSTRIAL DISTRICTS.
7. FIRE HYDRANTS WHEN REQUIRED ARE TO BE LOCATED OUTSIDE THE R-O-W IN A 5' BY 5' EASEMENT.

STREET AND RIGHT-OF-WAY WIDTHS

FUNCTIONAL CLASSIFICATION	RIGHT-OF-WAY	A PAVEMENT WIDTH	SIDEWALK WIDTH	PLANTER STRIP WIDTH
ALLEY RESIDENTIAL DISTRICT	20'	10'	N/A	N/A
ALLEY-COMM. INDUSTRIAL DISTRICT	20'	10'	N/A	N/A


DRAWN M.R.M.			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON	SCALE N.T.S.
DIV. TRANSPORTATION				DATE 2002
REV.	DATE	APPR.	ALLEY STREET SECTION	APPR.
				DWG. NO. 506



PAVEMENT WIDTH EXCEPTIONS:


1. A 28' WIDTH MAY BE ALLOWED WITHIN THE SLOPE HAZARD AREA WITH CITY ENGINEER'S APPROVAL.
2. THE SIDEWALK IS TO BE LOCATED NEXT TO THE CURB ON ALL CUL-DE-SAC BULBS AND THE ENTIRE LENGTH OF THE CUL-DE-SAC IN THE SLOPE HAZARD AREA.
3. THE SIDEWALK SHALL HAVE A MINIMUM 5' CLEAR OF ALL OBSTACLES, UNLESS APPROVED BY THE CITY ENGINEER.
4. NO FIRE HYDRANTS ARE TO BE LOCATED IN THE CUL-DE-SAC AREA.

DRAWN	MRM	COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON STANDARD CUL-DE-SAC		SCALE	N.T.S.
ENGR.	TRANSPORTATION			DATE	2002
REV.	DATE			APPR.	
				DWG. NO.	508





1. BRANCH TURNAROUND TO BE USED AT THE END OF A MINOR ACCESS STREET.
2. A "DEAD-END" SIGN SHALL BE POSTED AT ENTRANCE TO THE MINOR ACCESS STREET.
3. "NO PARKING" SHALL BE POSTED FOR THE ENTIRE MINOR ACCESS STREET.
4. THE MAXIMUM LENGTH OF THE MINOR ACCESS STREET SHALL BE 150 FT. TO THE END OF THE TURNAROUND.
5. NO FIRE HYDRANTS ARE TO BE LOCATED ON A MINOR ACCESS STREET WITH A BRANCH TURNAROUND.

DRAWN MRM			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON BRANCH TURNAROUND	SCALE N.T.S.
DIV. TRANSPORTATION				DATE 2002
REV.	DATE	APPR.		APPR.
				DWG. NO. 509




DRAWN			M.R.M.			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON			SCALE		N.T.S.	
DIV.			TRANSPORTATION						DATE		2002	
REV.	DATE	APPR.				APPR.			DWG. NO.		510	
						RESIDENTIAL DRIVEWAY APPROACH						



1. DISTANCE "A" VARIES WITH STREET FUNCTIONAL CLASSIFICATION.
2. EXPANSION JOINTS SHALL BE 1/2" WIDE AND CONSIST OF APPROVED PRE-FORMED FILLER.
3. CONTRACTION JOINTS SHALL BE 1/8" TO 1/4" WIDE. DEPTH OF THE JOINT SHALL BE A MINIMUM OF 1/3 THE THICKNESS OF THE CONCRETE.
4. ALL SURFACES SHALL BE LIGHTLY BROOMED AND EDGED IN A WORKMANLIKE MANNER.
5. SAW CUT EXISTING CURBS WHERE THEY ARE TO BE REMOVED, IF LESS THAN 3' TO EXISTING JOINT REMOVE TO JOINT. EXISTING A/C IN FRONT OF THE APPROACH SHALL BE SAW CUT AND REPLACED WITH HOT MIX.
6. CONCRETE SHALL BE 3000 PSI AT 28 DAYS.
7. SEE STANDARD DRAWING NUMBERS 518 AND 519 FOR CURB EXPOSURE DIMENSION 'e'.

DRAWN			MRM	<div>COMMUNITY DEVELOPMENT</div> <div>CITY OF SCAPPOOSE</div> <div>34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON</div> <div>COMMERCIAL DRIVEWAY APPROACH</div>	SCALE	N.T.S.
DIV. TRANSPORTATION					DATE	2002
REV.	DATE	APPR.			APPR.	
					DWG. NO. 511	




THIS TYPE OF APPROACH TO BE USED FOR HIGH VOLUME
TRAFFIC GENERATORS WITH APPROVAL OF CITY ENGINEER.

DRAWN MRM			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE	SCALE N.T.S.
DIV. TRANSPORTATION				DATE 2002
REV.	DATE	APPR.	34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON	APPR.
			CURB RETURN DRIVEWAY APPROACH	DWG. NO. 512


TYPICAL SIDEWALK DETAIL

(FOR LOCAL STREET)



1. LOCATION AND WIDTH OF SIDEWALK WILL VARY DEPENDING UPON FUNCTIONAL CLASSIFICATION OF THE STREET. SEE TYPICAL STREET SECTION DRAWINGS ST-500,ST-501,ST-502.
2. PCC SHALL BE 3300 PSI STRENGTH AT 28 DAYS.
3. EXPANSION JOINTS SHALL BE PLACED AT DRIVEWAY APPROACHES, CURB RETURNS AND AT ANY FIXED OBJECT WITHIN THE SIDEWALK AREA. JOINTING MATERIAL AT DRIVEWAYS SHALL CONSIST OF APPROVED FILLER AND SHALL NOT BE LESS THAN 1/2" WIDE.
4. CONTRACTION JOINTS SHALL BE PLACED AT ALL CHANGES OF DIRECTION, POINTS OF CURVATURE AND AT 15' (MAX) INTERVALS. JOINTS SHALL BE 1/8" TO 1/4" WIDE AND A MINIMUM DEPTH OF 1/3 THE THICKNESS OF THE CONCRETE.
5. ALL SURFACES SHALL BE TROWELED AND BROOMED IN A WORKMANLIKE MANNER. ALL CONTRACTION JOINTS SHALL BE STEEL TROWELED (3 IN. TYP.).


DRAWN			MRM			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON			SCALE		N.T.S.	
DIV. TRANSPORTATION									DATE		2002	
REV.		DATE		APPR.		TYPICAL SIDEWALK DETAIL			APPR.			
									DWG. NO.			513



1. PCC SHALL BE 3000 PSI STRENGTH AT 28 DAYS.
2. TWO SIDEWALK RAMPS PER CORNER ARE REQUIRED AT ALL NEW INTERSECTIONS.
3. A SINGLE DIAGONAL RAMP MAY BE USED AT ALTERATIONS ONLY, WHEN SITE CONSTRAINTS PROHIBIT INSTALLING TWO RAMPS AND APPROVED BY CITY ENGINEER.
4. REPLACEMENT CURBS MUST BE POURED AGAINST A VERTICAL EDGE OF REMAINING CURB.
5. CONCRETE IN A REPLACEMENT CURB SHALL NOT PROTRUDE PAST THE FACE OF THE CURB IN THE ASPHALT REPLACEMENT AREA.
6. HORIZONTAL AND VERTICAL ALIGNMENT SHALL BE WITHIN 1/8" IN 10 FEET.
7. USE DIAMOND PATTERN IN CENTER RAMP.
8. SEE STANDARD DRAWING NUMBERS 518 AND 519 FOR CURB EXPOSURE DIMENSION 'e'.

DRAWN	MRM	COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON SIDEWALK RAMP		SCALE	N.T.S.
DIV.	TRANSPORTATION			DATE	2002
REV.	DATE			APPR.	
				DWG. NO.	514

WHERE LIGHTING IS NEEDED
MEET IES STANDARDS FOR
PEDESTRIAN SCALE LIGHTING
— STYLE AND HEIGHT
MAY VARY (UP TO 16' HEIGHT)




1. ASPHALTIC CONCRETE (2 LIFTS)—1 1/2" CLASS "C" ON 1 1/2" CLASS "B".
2. AGGREGATE BASE — 1"—0 CRUSHED ROCK, 8" DEPTH.
3. SUBGRADE AND BASEROCK SHALL BE COMPACTED TO 95% RELATIVE DENSITY PER AASHTO T-180.

ACCESSWAY TYPE	PAVEMENT WIDTH MAXIMUM LENGTH 200'	SURFACE TYPE
NEIGHBORHOOD ACCESSWAY	5' — 12'	PCC OR A/C
PUBLIC / PRIVATE INTEGRATED ACCESSWAY	7' — 12'	PCC OR A/C
PARK / NATURAL AREA ACCESSWAY	8' — 12'	PCC, A/C, OR SOFT SURFACE

*NOTE: WHERE ACCESSWAYS CONTINUE ACROSS STREETS, ADA RAMPS SHALL BE REQUIRED



DRAWN	MRM	COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON PEDESTRIAN / BICYCLE ACCESSWAY DETAIL	SCALE	N.T.S.
DIV.	TRANSPORTATION		DATE	2002
REV.	DATE		APPR.	
			DWG. NO.	515



NOTE: DECORATIVE STANDARD BOLLARD MAY BE APPROVED BY THE MANAGER.
SEE STANDARD DETAIL DRAWING 515 FOR ACCESSWAY DETAIL

DRAWN			MRM			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE			SCALE		N.T.S.		
DIV.			TRANSPORTATION						DATE		2002		
REV.	DATE	APPR.	34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON						APPR.				
									DWG. NO.		516		
BOLLARD DETAIL													

BOLLARD DETAIL



4" CONVENTIONAL LETTERING

2" PLANK

2- 1/2" GALVANIZED BOLTS WITH WASHERS AND NUT OR TWO (2) 4 1/2" LAG BOLTS.

4"x6" POST PAINTED WHITE


THIS PORTION TO BE TREATED

CRUSHED AGGREGATE BACKFILL

A	B	C	D	E	F
40'	10'	5'MIN.	4'MIN.	20"	8"-12"
36'	9'	5'MIN.	4'MIN.	20"	8"-12"
32'	8'	5'MIN.	4'MIN.	20"	8"-12"

NOTES:


1. STRIPING SHALL BE ALTERNATING RED (RODDA #1249 OR EQUAL) AND WHITE STRIPES 6" IN WIDTH AT A 45 DEGREE ANGLE AND SHALL BE EITHER RETRO-REFLECTIVE TAPE OR PAINTED WITH A SEALED RETRO-REFLECTIVE SURFACE.
2. THIS BARRICADE SHALL CONFORM TO SECTION 3F-I, UNIFORM MANUAL ON TRAFFIC CONTROL DEVICES-FHWA.



DRAWN	M.R.M.
DIV.	TRANSPORTATION
REV.	DATE
	APPR.


COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE
 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON
STREET BARRICADE

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	517



1. PCC SHALL BE 3000 PSI STRENGTH AT 28 DAYS.
2. CONTRACTION JOINTS SHALL BE PLACED AT 15' MAX. SPACING.
3. EXPANSION JOINTS SHALL BE PLACED AT 45' MAX. SPACING AND AT ALL DRIVEWAYS AND CURB RETURNS.
4. CURB EXPOSURE SHALL BE 9" AT ALL CATCH INLETS.
5. DRAIN BLOCKOUT SHALL BE ABLE TO FIT 3" DIA. DRAIN PIPE AND PLACED WHERE DIRECTED.
6. ADD KEYWAY WHEN CURB IS PLACED AGAINST SIDEWALK.
7. CRUSHED BASE ROCK SHALL BE COMPACTED TO 95% RELATIVE DENSITY PER AASHTO T-180.
8. TYPE "C" CURB SHALL ONLY BE INSTALLED AT LOCATIONS (REPLACEMENT) TO MATCH EXISTING CURB TYPE.

DRAWN M.R.M.			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON TYPE "C" CURB	SCALE N.T.S.
DIV. TRANSPORTATION				DATE 2002
REV.	DATE	APPR.		APPR.
				DWG. NO. 518





1. PCC SHALL BE 3000 PSI STRENGTH AT 28 DAYS.
2. CONTRACTION JOINTS SHALL BE PLACED AT 15' MAX. SPACING.
3. EXPANSION JOINTS SHALL BE PLACED AT ALL DRIVEWAYS AND CURB RETURNS.
4. CURB EXPOSURE SHALL BE 8" AT ALL CATCH INLETS.
5. DRAIN BLOCKOUT SHALL BE SUFFICIENT FOR 3" DRAIN PIPE AND PLACED WHERE DIRECTED.
6. ADD KEYWAY WHEN CURB IS PLACED AGAINST SIDEWALK.
7. CRUSHED BASE ROCK SHALL BE COMPACTED TO 95% RELATIVE DENSITY PER AASHTO T-180.
8. WHEN A DRIVEWAY IS PLACED WHERE THERE IS AN EXISTING MONOLITHIC CURB MAKE A VERTICAL SAWCUT AT THE FACE OF CURB. REPLACE BACK PART OF CURB AND ADD DRIVEWAY WITH ONE CONTIGUOUS POUR.

DRAWN			M.R.M.			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE			SCALE		N.T.S.	
DIV.			TRANSPORTATION						DATE		2002	
REV.	DATE	APPR.				34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON			APPR.			
									DWG. NO.		519	
			MONOLITHIC CURB AND GUTTER									

MOUNTABLE CURB

TO BE USED FOR HIGH DENSITY DEVELOPMENT
WITH CITY ENGINEER'S APPROVAL




1. PCC SHALL BE 3000 PSI STRENGTH AT 28 DAYS.
2. CONTRACTION JOINTS SHALL BE PLACED AT 15' MAX. SPACING.
3. EXPANSION JOINTS SHALL BE PLACED AT 45' MAX. SPACING AND AT ALL DRIVEWAYS AND CURB RETURNS.
4. ADD KEYWAY WHEN SIDEWALK IS PLACED AGAINST CURB.
5. CRUSHED BASE ROCK SHALL BE COMPACTED TO 95% RELATIVE DENSITY PER AASHTO T-180.
6. ROOF DRAINS SHALL DRAIN DIRECTLY TO DRAINAGE CATCH BASINS.
7. ALTERNATE DESIGNS MAY BE APPROVED BY THE CITY ENGINEER.

DRAWN MRM			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON MOUNTABLE CURB	SCALE N.T.S.
DIV. TRANSPORTATION				DATE 2002
REV.	DATE	APPR.		APPR.
				DWG. NO. 520


ALTERNATE MOUNTABLE CURB

TO BE USED FOR HIGH DENSITY DEVELOPMENT
WITH CITY ENGINEER'S APPROVAL



1. PCC SHALL BE 3000 PSI STRENGTH AT 28 DAYS.
2. CONTRACTION JOINTS SHALL BE PLACED AT 15' MAX. SPACING.
3. EXPANSION JOINTS SHALL BE PLACED AT 45' MAX. SPACING AND AT ALL DRIVEWAYS AND CURB RETURNS.
4. ADD KEYWAY WHEN SIDEWALK IS PLACED AGAINST CURB.
5. CRUSHED BASE ROCK SHALL BE COMPACTED TO 95% RELATIVE DENSITY PER AASHTO T-180.
6. ROOF DRAINS SHALL DRAIN DIRECTLY TO DRAINAGE CATCH BASINS.
7. ALTERNATE DESIGNS MAY BE APPROVED BY THE CITY ENGINEER.

DRAWN ELS			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON MOUNTABLE CURB	SCALE N.T.S.
DIV.				DATE 3-12-2002
REV.	DATE	APPR.		APPR. ELS
				DWG. NO. 520A



1. MAINTAIN TOP OF CURB AT STANDARD ELEVATION. SET LOWER SIDE OF GRATE 0'-6" BELOW TOP OF CURB.
2. CONSTRUCT CATCH BASIN PER DRAWING 601B


DRAWN M.R.M.		
DIV. TRANSPORTATION		
REV.	DATE	APPR.

**COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE**

34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON


**MOUNTABLE CURB TRANSITION
SIDE INLET CATCH BASIN**

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	521




***JOINT TRENCH DETAIL (OPTIONAL)** N.T.S.


DRAWN			AJB			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE			SCALE			N.T.S.					
DIV.			TRANSPORTATION						DATE			2002					
REV.			DATE			APPR.			34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON			APPR.					
									TYPICAL UTILITY PLACEMENT DETAIL			DWG. NO.			522		



PLAN VIEW



STEPS 2, 3, & 4




STEP 1


- STEP 1 COVER EXISTING MANHOLE WITH BUILDING PAPER AND CONSTRUCT A/C PAVEMENT OVER TOP OF MANHOLE.
- STEP 2 SAW CUT AND REMOVE PAVEMENT AROUND MANHOLE 12" MIN. FROM MANHOLE FRAME.
- STEP 3 RAISE MANHOLE FRAME AND INSTALL CONCRETE RINGS TO FINISH PAVEMENT PROFILE AND CROSS SLOPE.
- STEP 4 BACKFILL WITH EARLY STRENGTH P.C.C. AND A/C TO DEPTHS AS DIRECTED.

DRAWN	MRM	COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON		SCALE	N.T.S.
DIV.	TRANSPORTATION			DATE	2002
REV.	DATE	APPR.		APPR.	
				DWG. NO.	523

MANHOLE ADJUSTMENT DETAIL





W260




SIGNS TO BE
INSTALLED BY OTHERS

SIGNING AND STRIPING PLAN



SECTION A-A



SECTION B-B

NOTES:

1. SPACING - SPEED HUMPS SHOULD BE PLACED ACCORDING TO THE ENGINEER'S EVALUATION OF THE PHYSICAL STREET SECTION AS WELL AS TRAFFIC OPERATIONS DATA. TYPICALLY, SPEED HUMPS SHOULD BE PLACED BETWEEN 300 AND 600 FEET APART.
2. TOLERANCE - THE TOLERANCE FOR SPEED HUMPS SHOULDN'T VARY BY MORE THAN .5" FROM THE CITY'S TEMPLATE.

DRAWN		MRM	
DIV.		TRANSPORTATION	
REV.	DATE	APPR.	

COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE

34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON


14FT. WIDE
MOUNTABLE SPEED BUMP

SCALE N.T.S.

DATE 2002


APPR.

DWG. NO. 524




SIGNING AND STRIPING PLAN
NTS


SIGNS TO BE
INSTALLED BY OTHERS



SECTION A-A




SECTION B-B




NOTES:

1. SPACING - SPEED HUMPS SHOULD BE PLACED ACCORDING TO THE ENGINEER'S EVALUATION OF THE PHYSICAL STREET SECTION AS WELL AS TRAFFIC OPERATIONS DATA. TYPICALLY, SPEED HUMPS SHOULD BE PLACED BETWEEN 300 AND 600 FEET APART.
2. TOLERANCE - THE TOLERANCE FOR SPEED HUMPS SHOULDN'T VARY BY MORE THAN .5" FROM THE CITY'S TEMPLATE.

DRAWN MRM			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON 22 FT. WIDE SPEED HUMP	SCALE N.T.S.
DIV. TRANSPORTATION				DATE 2002
REV.	DATE	APPR.		APPR.
				DWG. NO. 525




LID



PLACEMENT OF BRASS CAP AND MONUMENT BOX SHALL FOLLOW
COLUMBIA COUNTY SURVEYORS OFFICE STANDARDS.

DRAWN			MRM			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON STANDARD MONUMENT BOX	SCALE	N.T.S.
DIV. TRANSPORTATION							DATE	2002
REV.	DATE	APPR.					APPR.	
							DWG. NO.	526




1. MOUNT LUMINAIRE 25-30 FT. ABOVE GROUND.
 2. ON STREETS WITH A PLANTER STRIP BETWEEN THE CURB AND SIDEWALK, MOUNT POLE 2FT. BEHIND FACE OF CURB.
- ON STREETS WITH NO PLANTER STRIP BETWEEN THE CURB AND SIDEWALK, MOUNT POLE 6" BEHIND SIDEWALK.

DRAWN			MRM	COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON STANDARD STREET LIGHT DETAIL	SCALE	N.T.S.
DIV.			TRANSPORTATION		DATE	2002
REV.	DATE	APPR.			APPR.	
					DWG. NO.	527

STANDARD STREET LIGHT DETAIL

LUMINAIRE MOUNTED ON EXISTING POLE



POLE: EXISTING WOOD POLE

WATTAGE REQUIREMENTS WILL VARY DEPENDING ON LIGHTING REQUIREMENTS.


ITEM	DESCRIPTION
A	Bolt, Mach., Galv., 5/8" x 12"
B	Washer, Flat 3/16" x 2-1/4"
C	Screw, Lag, 1/2" x 4-1/2"
F	Arm, Mast, Upswept – 8'*
K	Bushing, Insulation 1-1/4"
L	Staples – Flat Head Type
M	Wire, #10 TC 3 Conductor

MAST ARM INSTALLATION DRAWING

NEW CONSTRUCTION WHERE VOLTAGE
IS LIMITED TO 300 VOLTS.



*ACTUAL MAST ARM LENGTH DEPENDS ON LOCATION

DRAWN			MRM		<div>COMMUNITY DEVELOPMENT</div> <div>CITY OF SCAPPOOSE</div> <div>34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON</div> <div>MAST ARM DETAIL</div>	SCALE	N.T.S.
ENGR.			TRANSPORTATION			DATE	2002
REV.	DATE	APPR.				APPR.	
						DWG. NO.	529



1. ANCHOR SHALL BE COVERED BY DUCT TAPE ON ALL SIDES AND END.
2. ANCHOR SHALL BE SET IN 22" OF CONCRETE UNLESS IN SIDEWALK.
3. IF RECEIVER TUBE IS SET IN SIDEWALK IT SHALL BE 2'-2" DEEP & BACKFILLED WITH COMPACTED FILL, THEN CONCRETE FROM BOTTOM TO TOP OF WALK.
4. SIGN PLACEMENT IN SIDEWALK SHALL ALLOW FOR 5' CLEAR PASSAGE & SIGN POST SHALL BE 12" FROM BACK OF CURB.
5. POST SHALL BE SPRAYED WITH ANTI-SEIZE ON THE LAST 2'-6".

DRAWN	MRM	COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE		SCALE	N.T.S.
DIV.	TRANSPORTATION			DATE	2002
REV.	DATE	APPR.	34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON		APPR.
			STANDARD SIGNPOST		DWG. NO. 531



DRAWN AJB		
DIV. TRANSPORTATION		
REV.	DATE	APPR.

COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE

34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON


TREE WELL DETAIL

SCALE	N.T.S.
-------	--------


DATE	2002
------	------

APPR.

DWG. NO.	533
----------	-----



PLAN VIEW





NOTE:

ALL CONC. TO BE 3,000 PSI AT 28 DAYS. PROVIDE 1/2" EXPANSION JOINT AT CENTER OF CROSSWALK OR AT 15' O.C.


SECTION

DRAWN			AJB		COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON PAVER CROSSWALK DETAIL	SCALE		N.T.S.		
DIV. TRANSPORTATION						DATE		2002		
REV.	DATE	APPR.		APPR.		DWG. NO.		534		



NOTE:
PLACE 1/2" EXPANSION JOINT AT CENTER


DRAWN			AJB	COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON	SCALE	N.T.S.
DIV. TRANSPORTATION					DATE	2002
REV.	DATE	APPR.			APPR.	
					DWG. NO.	535
				CONCRETE CROSSWALK DETAIL		



DRAWN		
DIV. STORMWATER		
REV.	DATE	APPR.
REV	REV-DATE	

COMMUNITY DEVELOPMENT		
CITY OF SCAPPOOSE		
34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON		
CATCH BASIN		

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	601-A



DRAWN	DRAWN	
DIV.	STORMWATER	
REV.	DATE	APPR.
REV	REV-DATE	

COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE
34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON
CATCH BASIN
SECTION AND CURB DETAIL


SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	601B




TABLE 601-C	CURB TYPE	
	TYPE "C"	MONOLITHIC
Y1	9"	8"
Y2	5 3/4"±	4 3/4"±
Y3	8 1/2"	7 1/2"
Y4	16"	12"

DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON CURB DETAIL AT CATCH BASIN	SCALE	N.T.S.
DIV. STORMWATER				DATE	2002
REV.	DATE	APPR.		APPR.	
REV	REV-DATE			DWG. NO.	601C

NOTE:
USE VERTICAL BEADS IN CORNERS,
FILLET WELD JOINT ON BOTTOM OF
FRAME. GRATE MUST REST FLAT ON
FRAME SURFACE.



SECTION A-A



NOTE:
3/8" ROUND OR
RECTANGULAR
CROSS BARS
SHALL BE FILLET
WELDED, RESISTANCE
WELDED OR
ELECTROFORGED
TO BEARING BARS


TYP. 3/16"


SECTION B-B

DRAWN	DRAWN
DIV.	STORMWATER
REV.	DATE
REV	REV-DATE


COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE
34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON
FRAME AND GRATE

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	603





DRAWN			COMMUNITY DEVELOPMENT			SCALE N.T.S.	
DIV. STORMWATER			CITY OF SCAPPOOSE			DATE 2002	
REV.	DATE	APPR.	34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON			APPR.	
REV	REV-DATE		STORM SUMP SYSTEM AND SEDIMENTATION MANHOLE (TYPICAL RETROFIT INSTALLATION)			DWG. NO. 605	



DRAWN	DRAWN	
DIV.	STORMWATER	
REV.	DATE	APPR.
REV	REV-DATE	

**COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE**

34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON


POLYPROPYLENE HANGING LADDER

SCALE N.T.S.


DATE 2002

APPR.


DWG. NO. 605A



DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON INLET – MANHOLE STANDARD	SCALE	N.T.S.
DIV. STORMWATER				DATE	2002
REV.	DATE	APPR.		APPR.	
REV	REV-DATE			DWG. NO.	606A



COMBINATION CURB INLET




OFFSET RECTANGULAR TOP SLAB

NOTES:

1. REINFORCING FOR INLET UNIT 3 EA. #4 HORIZONTAL BARS.
2. REINFORCING FOR TOP UNIT 2 EA. #3 HORIZONTAL BARS.
3. REINFORCING FOR INLET SLOPED BASE, 4" X 4" MESH.
4. GUTTER IS TAPERED DOWN TO GRATE INLET.
5. TOP SLAB REINFORCING
 - #4 DEFORMED REBAR AROUND OPENING.
 - DIAGONALLY ON BOTH SIDES OF OPENING @ 6" O.C. IN BOTH DIRECTIONS.

DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON INLET—MANHOLE COMBINATION CURB INLET	SCALE	N.T.S.
DIV. STORMWATER				DATE	2002
REV.	DATE	APPR.		APPR.	
REV	REV—DATE			DWG. NO.	606B



DRAWN			DRAWN		
DIV.			STORMWATER		
REV.	DATE	APPR.	REV.	DATE	APPR.
REV	REV-DATE		REV	REV-DATE	
<p align="center">COMMUNITY DEVELOPMENT</p> <p align="center">CITY OF SCAPPOOSE</p> <p align="center">34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON</p> <p align="center">INLET - MANHOLE</p> <p align="center">ALTERNATE TOP</p>					
			SCALE N.T.S.		
			DATE 2002		
			APPR.		
			DWG. NO. 606C		

FRAME AND COVER
SET IN MORTAR
SEE STD. DETAILS
307, 308 & 309
AS CALLED OUT
ON PLANS

MANHOLE ACCESS
FROM ABOVE

24" MAX.

36" MAX.

1/2" BOLT
(STAINLESS
STEEL)

12"

GALV. CHAIN
200# CAPACITY
SLACK WHEN
GATE IS DOWN

12" MIN.

3"

30" MIN.

FLOW

ARMCO MODEL
160 TURNOUT
GATE OR APP-
PROVED EQUAL,
TO BE WATER-
TIGHT IN PLACE.

60" MIN.

5" MIN.

6" MIN.

6" MIN.

SECTION A-A

36" MIN.

INVERT
ELV.

MULTI-ORIFICE ELBOWS TO BE
LOCATED TO ASSURE LADDER
CLEARANCE PROVIDE REMOVABLE
WATER TIGHT COUPLING

VARIES

FABRICATED SOLID WALL
HDPE CROSS PER ASTM
D-1248 SDR 26

FLOW


APPROVED PIPE
12" MIN.

FLEXIBLE COUPLING

NON SHRINK GROUT
(TYPICAL)

COMPACTED GRANULAR
MATERIAL

RESTRICTOR PLATE (FOR
FLOW CONTROL ONLY)
ORIFICE DIA. = _____



PLAN

INFLOW LINE(S)
PER PLAN


6" MIN.

OVERFLOW EL.

DRAWN	DRAWN
DIV. STORMWATER	
REV.	DATE APPR.
REV	REV-DATE

COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE
34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON
FLOW CONTROL MANHOLE



SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	607




1. CONCRETE SHALL ATTAIN A MINIMUM COMPRESSIVE STRENGTH OF 3000 P.S.I. IN 28 DAYS

2. FOR FRAME & GRATE DETAIL SEE STD. DWG NO. 609-A

3. WHERE PRECAST INLETS ARE USED AS AN ALTERNATIVE TO CAST IN PLACE INLETS, A 4" COMPACTED LEVELING BED OF 1/4"-0" CRUSHED AGGREGATE SHALL BE PROVIDED



SECTION A-A






SECTION B-B

DRAWN		
DIV. STORMWATER		
REV.	DATE	APPR.
REV	REV-DATE	

COMMUNITY DEVELOPMENT		
CITY OF SCAPPOOSE		
34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON		
DITCH INLET		
TYPE D		

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	609






DRAWN		DRAWN	
DIV.		DEPT	
REV.	DATE	APPR.	

COMMUNITY DEVELOPMENT
CITY OF SCAPPOOSE

34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON

CG-2 DOUBLE CATCH BASIN

SCALE	N.T.S.
DATE	2002
APPR.	
DWG. NO.	610




SECTION B-B

NOTES:

1. #3 BARS SHALL BE PLACED DURING CURB CONSTRUCTION.
2. ALL BARS SHALL BE PLACED 1 1/2" CLEAR OF NEAREST FACE OF CONCRETE UNLESS SHOWN OR OTHERWISE NOTED.
3. ALL BAR SPLICES LENGTHS SHALL BE A MIN. 20 DIA.
4. CLASS 3000 CONCRETE SHALL BE USED IN ALL INLETS.


DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON CG-2 DOUBLE CATCH BASIN CURB SECTION			SCALE N.T.S.	
DIV. DEPT						DATE 2002	
REV.	DATE	APPR.				APPR.	
						DWG. NO. 610A	



NOTE:
USE VERTICAL BEADS IN CORNERS, FILLET WELD JOINT ON
BOTTOM OF FRAME. GRATE MUST REST FLAT ON FRAME SURFACE.

PLAN (FRAME)

SECTION A-A



PLAN (GRATE)
TYPE 2 GRATE

DRAWN			COMMUNITY DEVELOPMENT CITY OF SCAPPOOSE 34485 E. COLUMBIA AVE., PO BOX "P", SCAPPOOSE, OREGON CG-2 FRAME AND GRATE	SCALE	N.T.S.
DIV.				DATE	2002
REV.	DATE	APPR.		APPR.	
				DWG. NO.	611